

30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Pushbutton Non-Illuminated Flush Button Plastic Cap, Black 2 Position Momentary with 2 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



Figure similar

Enclosure	
Number of command points	1
Delivery state	
<ul style="list-style-type: none"> as a kit 	No
Actuator	
Design of the operating mechanism	Pushbutton
Color	
<ul style="list-style-type: none"> of the actuating element 	black
Material of the actuating element	plastic
Number of contact modules	2
Type of unlocking device	without
Number of switching positions	2
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	black

General technical data	
Product function	
• positive opening	Yes
Product component	
• Light source	No
Insulation voltage	
• rated value	600 V
Surge voltage resistance rated value	4 kV
Protection class IP	IP66
• of the terminal	IP20
Thermal current	10 A
Operating voltage	
• at AC	
— at 60 Hz rated value	5 ... 600 V
• at DC rated value	5 ... 600 V
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	2
Number of NO contacts for auxiliary contacts	0
Operating current at AC-15	
• at 110 V rated value	60 A
• at 230 V rated value	30 A
• at 400 V rated value	15 A
• at 500 V rated value	12 A
Connections/Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	
• with screw-type terminals	8 lbf·in
Ambient conditions	
Ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C
Installation/ mounting/ dimensions	
Shape of the installation opening	round
Mounting height	21 mm
Installation width	54 mm
Installation depth	35 mm
Certificates/approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PX8A1G>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PX8A1G>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52PX8A1G>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PX8A1G&lang=en

last modified:

05/08/2019