

SIMATIC IFP2200, Flat Panel 22" display (16:9), Multitouch, neutral design, black without logo symmetric frame, Extended Version max. 30m, 1920x1080 pixel, for 24V DC, Displayport / DVI interface incl. DVI/USB cable 1,8 m



Figure similar

General information	
Product type designation	IFP2200
Short designation	Flat Panel 22" multi-touch ext.
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	21.5 in
Screen diagonal [cm]	56 cm
Display width	476 mm
Display height	268 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	170° x 170°
Resolution (pixels)	
• Horizontal image resolution	1 920 Pixel
• Vertical image resolution	1 080 Pixel
• Pixel size, horizontal	0.2475 mm
• Pixel size, vertical	0.2475 mm

General features	
• Brightness/contrast	250 cd/m ² / 1 000:1
• non-reflective and tempered mineral glass screen	Yes
• Detachable from computer unit	30 m
• Luminance	250 cd/m ²
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Keyboard fonts	
• Function keys	No
— Number of function keys	0
Touch operation	
• Design as touch screen	Yes; Projective-capacitive
• Monitor keyboard	Yes
Installation type/mounting	
Design	Built-in unit
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	35°
maximum permitted backward tilt angle from vertical	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; PELV / SELV floating
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Power loss	
Power loss, typ.	40 W
Power loss, max.	65 W
Interfaces	
USB on the rear	Yes; 2x onboard
Connection for keyboard/mouse	USB
Video interfaces	
• analog video signal (VGA)	No
• DVI-D	Yes
• DisplayPort	Yes; DisplayPort V1.1
Touch interfaces	
• USB	Yes
Degree and class of protection	

IP (at the front)	
• IP65 at front	Yes
IP (rear)	
• IP20 rear	Yes
NEMA (front)	
• Enclosure Type 4 at the front	Yes
• Enclosure Type 4x at the front	Yes
• Enclosure Type 12 at the front	Yes
• NEMA4 at the front	No
• NEMA4X at the front	No

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes; cULus, cUL
cULus	Yes; Corresponds to UL 508
RCM (formerly C-TICK)	Yes
KC approval	Yes

Use in hazardous areas

• ATEX Zone 2	No; Available soon
• ATEX Zone 22	No; Available soon

Marine approval

• Germanischer Lloyd (GL)	No; Available soon
• American Bureau of Shipping (ABS)	No; Available soon
• Bureau Veritas (BV)	No; Available soon
• Det Norske Veritas (DNV)	No; Available soon
• Lloyds Register of Shipping (LRS)	No; Available soon
• Nippon Kaiji Kyokai (Class NK)	No; Available soon

Ambient conditions

Ambient temperature during operation

• min.	0 °C
• max.	45 °C; Vertical installation (horizontal)

Ambient temperature during storage/transportation

• min.	-20 °C
• max.	60 °C

Relative humidity

• Operation, max.	95 %; no condensation
-------------------	-----------------------

Vibrations

• Vibration load in operation	10 m/s ²
• Vibration load during transport/storage	10 m/s ²

Shock testing

• Shock load during operation	150 m/s ²
• Shock load during transport/storage	150 m/s ²

Mechanics/material

Enclosure material (front)

- Glass

Yes

Dimensions

Width of the housing front

529 mm

Height of housing front

331 mm

Mounting cutout, width

513 mm; Tolerance: +1 mm

Mounting cutout, height

315 mm; Tolerance: +1 mm

Overall depth

72 mm

Weights

Weight without packaging

6.7 kg

Weight incl. packaging

6.8 kg

last modified:

03/14/2020