

Metal, selector switch Maintained, short lever 1NC + 1NO left, 1NC right position , C Cam 3 position Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Enclosure	
Number of command points	1
Delivery state	No
<ul style="list-style-type: none"> <li>as a kit</li> </ul>	No
Actuator	
Material of the actuating element	plastic
Number of contact modules	3
Type of unlocking device	rotate-to-unlatch mechanism
Number of switching positions	3
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
General technical data	
Product function	Yes
<ul style="list-style-type: none"> <li>positive opening</li> </ul>	Yes
Product component	No
<ul style="list-style-type: none"> <li>Light source</li> </ul>	No
Insulation voltage	600 V
<ul style="list-style-type: none"> <li>rated value</li> </ul>	600 V
Protection class IP	IP66
<ul style="list-style-type: none"> <li>of the terminal</li> </ul>	IP20
Operating frequency maximum	600 1/h
Thermal current	10 A
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	2
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	60 A
<ul style="list-style-type: none"> <li>at 110 V rated value</li> <li>at 500 V rated value</li> </ul>	12 A
Connections/ Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m

<b>Tightening torque [lbf·in]</b>	
<ul style="list-style-type: none"> <li>with screw-type terminals</li> </ul>	8 lbf·in
<b>Ambient conditions</b>	
<b>Ambient temperature</b>	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-35 ... +70 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C
<b>Installation/ mounting/ dimensions</b>	
<b>Shape of the installation opening</b>	round
<b>Certificates/ approvals</b>	
<b>Further information</b>	
<b>Information- and Downloadcenter (Catalogs, Brochures,...)</b> <a href="http://www.siemens.com/sirius/catalogs">www.siemens.com/sirius/catalogs</a>	
<b>Industry Mall (Online ordering system)</b> <a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2CABJ2K1">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2CABJ2K1</a>	
<b>Cax online generator</b> <a href="http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=US2:52SA2CABJ2K1">http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=US2:52SA2CABJ2K1</a>	
<b>Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)</b> <a href="https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2CABJ2K1">https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2CABJ2K1</a>	
<b>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)</b> <a href="http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2CABJ2K1&amp;lang=en">http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2CABJ2K1&amp;lang=en</a>	
<b>last modified:</b>	11/15/2019