

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8163-1AD03-0BA2



Figure similar

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \varphi$	I_{μ} [A]	
Y	ALM 400V	25.0	208.0	55.0	343	39.2	1,150	600	151.0	6,500.0	243.0	60	0.915	0.88	17.5
	BLM/SLM 400V	22.0	210.0	55.0	300	34.2	1,000	600	151.0	6,500.0	243.0	60	0.909	0.89	17.3
	ALM/BLM/SLM 480V	28.0	198.0	52.0	400	45.8	1,350	600	151.0	6,500.0	243.0	60	0.924	0.88	17.7

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Plain shaft
Encoder system	Without encoder

Physical constants

Thermal time constant	35 min
Moment of inertia	0.216 kgm ²
Weight (approx.)	196 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk863

Cooling data and sound pressure level

Airflow, min.	0.16 m ³ /s
Sound pressure level L _{pA} (1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	200 Pa

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm