



Catalog No. TG4326

Description: 600A 3P GD N1 240V FUSIBLE

UPC No 783164008722

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG4326



Representative Image

Descriptors

Category	General Duty
----------	--------------

Specifications

Amperage	600 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	(2) 4-500
240 Vac, NEC Std, 3-ph	75
240 Vac, Time Delay, 3-ph	100
GSA Compliance	Yes

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	49.9
Depth	9
Width	22.9
Weight	126

