

30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Metal Operator, Round Push-Pull Operator Non-Illuminated Mushroom Head Cap Large 2 1/2" (63.5 mm) Plastic, Red 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

|                              |                |
|------------------------------|----------------|
| <b>Design of the product</b> | Actuator round |
|------------------------------|----------------|

### Enclosure

|  |    |
|--|----|
| <b>Number of command points</b>                            | 1  |
| <b>Delivery state</b>                                      | No |
| <ul style="list-style-type: none"> <li>as a kit</li> </ul> |    |

### Actuator

|  |                           |
|--|---------------------------|
| <b>Material of the actuating element</b> | plastic                   |
| <b>Type of unlocking device</b>          | pull-to-unlatch mechanism |
| <b>Number of switching positions</b>     | 3                         |

### Front ring

|                                     |          |
|-------------------------------------|----------|
| <b>Product component front ring</b> | Yes      |
| <b>Design of the front ring</b>     | standard |
| <b>Material of the front ring</b>   | metal    |
| <b>Color of the front ring</b>      | chrome   |

### Holder

|                               |       |
|-------------------------------|-------|
| <b>Material of the holder</b> | Metal |
|-------------------------------|-------|

### General technical data

|  |      |
|--|------|
| <b>Product component</b>                                       |      |
| <ul style="list-style-type: none"> <li>Light source</li> </ul> | No   |
| <b>Degree of pollution</b>                                     | 1    |
| <b>Protection class IP</b>                                     | IP66 |

### Ambient conditions

|  |                |
|--|----------------|
| <b>Ambient temperature</b>   |                |
| <ul style="list-style-type: none"> <li>during operation</li> </ul> | -35 ... +70 °C |
| <ul style="list-style-type: none"> <li>during storage</li> </ul>   | -40 ... +85 °C |

### Installation/ mounting/ dimensions

|  |       |
|--|-------|
| <b>Shape of the installation opening</b> | round |
|--|-------|

### Certificates/ approvals

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)  
[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP7V2>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP7V2>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP7V2>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52PP7V2&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP7V2&lang=en)

last modified:

11/15/2019