

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7103-5AF71-1EB2

No image available for this configuration.

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data

Rated speed (100 K)	3000 rpm
Number of poles	8
Rated torque (100 K)	14.0 Nm
Rated current	12.0 A
Static torque (60 K)	30.00 Nm
Static torque (100 K)	36.0 Nm
Stall current (60 K)	22.80 A
Stall current (100 K)	27.50 A
Moment of inertia	118.000 kgcm ²
Efficiency	93.0 %

Physical constants

Torque constant	1.35 Nm/A
Voltage constant at 20° C	86.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.09 Ω
Rotating field inductance	2.0 mH
Electrical time constant	22.20 ms
Mechanical time constant	1.55 ms
Thermal time constant	65 min
Shaft torsional stiffness	149000 Nm/rad
Net weight of the motor	32.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1.5
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	with holding brake
Shaft extension	Feather key
Encoder system	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface

MLFB-Ordering data

1FK7103-5AF71-1EB2

Figure similar

Optimum operating point

Optimum speed 2500 rpm

Optimum power 5.4 kW

Limiting data

Max. permissible speed (mech.) 5000 rpm

Max. permissible speed (inverter) 6700 rpm

Maximum torque 108.0 Nm

Maximum current 84.0 A

Holding brake

Holding brake version Permanent-magnet brake

Holding torque 43.0 Nm

Power supply voltage DC 24 V \pm 10 %

Coil current 1.0 A

Opening time 300 ms

Closing time 70 ms

Highest braking work 3380 J

Recommended Motor Module

Rated inverter current 30 A

Maximum inverter current 56 A

Maximum torque 73.00 Nm