

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7032-2AK74-1AB1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data | | Mechanical data | | | |
|--|-------------------------|-----------------------------|------------------------------------|------------------------|--|
| Rated speed (100 K) | 6000 rpm | Motor type | Permanent-magnet synchronous motor | | |
| Number of poles | 6 | Motor type | Compact | | |
| Rated torque (100 K) | 0.8 Nm | Shaft height | 36 | | |
| Rated current | 1.4 A | Cooling | Natural cooling | | |
| Static torque (60 K) | 0.95 Nm | Radial runout tolerance | 0.035 mm | | |
| Static torque (100 K) | 1.1 Nm | Concentricity tolerance | 0.08 mm | | |
| Stall current (60 K) | 1.40 A | Axial runout tolerance | 0.08 mm | | |
| Stall current (100 K) | 1.70 A | Vibration severity grade | Grade A | | |
| Moment of inertia | 0.750 kgcm ² | Connector size | 1 | | |
| Efficiency | 88.0 % | Degree of protection | IP65 | | |
| <th colspan="2">Physical constants</th> <td>Design acc. to Code I</td> <td>IM B5 (IM V1, IM V3)</td> | | Physical constants | | Design acc. to Code I | IM B5 (IM V1, IM V3) |
| | | Torque constant | 0.67 Nm/A | Temperature monitoring | Pt1000 temperature sensor |
| | | Voltage constant at 20° C | 45.0 V/1000*min ⁻¹ | Electrical connectors | Connectors for signals and power rotatable |
| | | Winding resistance at 20° C | 5.05 Ω | Color of the housing | Standard (Anthracite RAL 7016) |
| | | Rotating field inductance | 17.3 mH | Holding brake | with holding brake |
| | | Electrical time constant | 3.45 ms | Shaft extension | Feather key |
| | | Mechanical time constant | 2.20 ms | Encoder system | Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track |
| | | Thermal time constant | 25 min | | |
| | | Shaft torsional stiffness | 4100 Nm/rad | | |
| | | Net weight of the motor | 3.1 kg | | |



Figure similar

MLFB-Ordering data

1FK7032-2AK74-1AB1

Optimum operating point

| | |
|---------------|----------|
| Optimum speed | 6000 rpm |
| Optimum power | 0.5 kW |

Limiting data

| | |
|-----------------------------------|-----------|
| Max. permissible speed (mech.) | 10000 rpm |
| Max. permissible speed (inverter) | 10000 rpm |
| Maximum torque | 4.5 Nm |
| Maximum current | 7.0 A |

Holding brake

| | |
|-----------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 1.9 Nm |
| Power supply voltage | DC 24 V \pm 10 % |
| Coil current | 0.3 A |
| Opening time | 50 ms |
| Closing time | 30 ms |
| Highest braking work | 40 J |

Recommended Motor Module

| | |
|--------------------------|---------|
| Rated inverter current | 3 A |
| Maximum inverter current | 9 A |
| Maximum torque | 4.50 Nm |