

circuit breaker VL1250L very high breaking capacity I_{cu}=100kA, 415V AC 3-pole, line protection trip unit ETU22, LSIG 3 phases/4 lines with connecting cable I_n=1250A, rated current I_R=500...1250A, overload protection, I_{SD}=1.5 to 9xI_R, I_I=10xI_N short-circuit protection without auxiliary release ETU communication-capable without auxiliary/alarm switch

Model	
type of the driving mechanism motor drive	No
design of the overcurrent release	ETU22
General technical data	
number of poles	3
size of the circuit-breaker	3VL7
mechanical service life (operating cycles) typical	3 000
electrical endurance (operating cycles) typical	1 500
utilization category	A
performance class for circuit breaker	N
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750	Q
operating frequency maximum	30 1/s
Voltage	
Rated operational voltage U _e max.	690 V
<ul style="list-style-type: none"> insulation voltage rated value insulation voltage (U_i) at AC rated value 	800 V
surge voltage resistance rated value	8 kV
operating voltage <ul style="list-style-type: none"> rated value maximum for main current circuit at AC at 50 Hz maximum for main current circuit at AC at 60 Hz maximum 	690 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LSIG
Main circuit	
operating frequency <ul style="list-style-type: none"> 1 rated value 2 rated value 	50 Hz
	60 Hz
Auxiliary circuit	
number of CO contacts for auxiliary contacts	0
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
Suitability	
suitability for use	system/generator protection
Adjustable parameters	
adjustable current response value current of the current-dependent overload release initial value	500 A
Product details	
product component <ul style="list-style-type: none"> trip indicator auxiliary switch voltage trigger undervoltage release undervoltage release with leading contact 	No
	No
	No
	No
	No
product extension optional motor drive	Yes
Product function	
product function	

• of thermal overload trip unit	adjustable
• grounding protection	Yes
• for neutral conductors short-circuit and overload proof	No
• overload protection	Yes

Short circuit

operating short-circuit current breaking capacity (Ics)	
• at 240 V rated value	100 kA
• at 415 V rated value	50 kA
• at 500 V rated value	38 kA
• at 690 V rated value	17 kA
maximum short-circuit current breaking capacity (Icu)	
• at 240 V rated value	200 kA
• at 415 V rated value	100 kA
• at 440 V rated value	75 kA
• at 480 V according to NEMA rated value	65 kA
• at 500 V rated value	50 kA
• at 600 V according to NEMA rated value	35 kA
• at 690 V rated value	35 kA

Connections

arrangement of electrical connectors for main current circuit	front side
type of connectable conductor cross-sections for auxiliary contacts	
• solid	0.75 ... 1.5 mm ²
• finely stranded with core end processing	0,75 ... 1.0 mm ²
type of electrical connection for main current circuit	screw-type terminals

Mechanical Design

height	406.5 mm
width	228.5 mm
depth	333.5 mm
fastening method	fixed mounting

Environmental conditions

ambient temperature during operation	
• minimum	-25 °C
• maximum	70 °C
ambient temperature during storage	
• minimum	-40 °C
• maximum	80 °C

Approvals Certificates

General Product Approval	Test Certificates
--------------------------	-------------------



EG-Konf.

[Confirmation](#)



CCC



[Special Test Certificate](#)

Marine / Shipping	other
-------------------	-------



[Miscellaneous](#)

[Confirmation](#)

[Miscellaneous](#)

Dangerous Good	Environment
----------------	-------------

[Transport Information](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL7712-3MH36-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL7712-3MH36-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL7712-3MH36-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

12/23/2020 

