

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7108-5WB71-1DA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	1500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact
Rated torque (100 K)	125.0 Nm	Shaft height	100 mm
Rated current	40.3 A	Cooling	Water cooling
Static torque (60 K)	100.00 Nm	Radial runout tolerance	N
Static torque (100 K)	125.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	31.6 A	Degree of protection	IP64
Stall current (100 K)	39.0 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0265000 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	94.0 %		
Physical constants		Color of the housing	
Torque constant	3.16 Nm/A	Holding brake version	no value
Voltage constant at 20° C	199.5 V/1000*min ⁻¹	Shaft end type	Fitted key and keyway
Winding resistance at 20° C	0.11 Ω	Sensor design	Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits
Rotating field inductance	2.7 mH	Electrical connectors	Connector turnable
Electrical time constant	24.00 ms	Connector size	1.5
Mechanical time constant	0.90 ms		
Thermal time constant	2 min		
Shaft torsional stiffness	96000 Nm/rad		
Net weight of the motor	68.6 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7108-5WB71-1DA0



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	1500 rpm	Rated inverter current	45 A
Optimum power	19.6 kW	Maximum inverter current	85 A
Limiting data		Maximum torque	249.50 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	2900 rpm		
Maximum torque	330.0 Nm		
Maximum current	120.5 A		