

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7034-5AK71-1VG5

No image available for this configuration.

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data

Rated speed (100 K)	6000 rpm
Number of poles	6
Rated torque (100 K)	1.0 Nm
Rated current	1.3 A
Static torque (60 K)	1.35 Nm
Static torque (100 K)	1.6 Nm
Stall current (60 K)	1.60 A
Stall current (100 K)	1.90 A
Moment of inertia	0.900 kgcm ²
Efficiency	88.0 %

Physical constants

Torque constant	0.86 Nm/A
Voltage constant at 20° C	55.0 V/1000*min ⁻¹
Winding resistance at 20° C	4.50 Ω
Rotating field inductance	16.5 mH
Electrical time constant	3.70 ms
Mechanical time constant	1.60 ms
Thermal time constant	30 min
Shaft torsional stiffness	5500 Nm/rad
Net weight of the motor	3.7 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	36
Cooling	Natural cooling
Radial runout tolerance	0.035 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft extension	Plain shaft
Encoder system	Encoder AM15DQ: absolute encoder 15 bits (resolution 32768, encoder-internal 16 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

MLFB-Ordering data

1FK7034-5AK71-1VG5

Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	6000 rpm	Rated inverter current	3 A
Optimum power	0.6 kW	Maximum inverter current	6 A
Limiting data		Maximum torque	4.90 Nm
Max. permissible speed (mech.)	10000 rpm		
Max. permissible speed (inverter)	10500 rpm		
Maximum torque	6.5 Nm		
Maximum current	8.0 A		