

30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 6V AC/DC Incandescent Lamp Less Mushroom Head Cap 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



Figure similar

| | |
|--|----------------|
| Design of the product | Actuator round |
| Enclosure | |
| Number of command points | 1 |
| Delivery state | No |
| • as a kit | |
| Actuator | |
| Product extension optional Light source | Yes |
| Type of unlocking device | without |
| Number of switching positions | 3 |
| Front ring | |
| Product component front ring | Yes |
| Design of the front ring | standard |
| Material of the front ring | metal |
| Color of the front ring | black |
| Holder | |
| Material of the holder | Metal |

| Contact block/ lampholder | |
|---|----------------------|
| socket type | BA 9s with lamp |
| Number of lampholders | 1 |
| Display | |
| Number of LED modules | 0 |
| General technical data | |
| Product component | |
| • lamp transformer | No |
| • Light source | Yes |
| Degree of pollution | 1 |
| Type of voltage | |
| • of the operating voltage | AC/DC |
| • of the input voltage | AC/DC |
| Surge voltage resistance rated value | 4 kV |
| Protection class IP | IP66 |
| • of the terminal | IP20 |
| Operating voltage | |
| • at AC | |
| — at 60 Hz rated value | 6 ... 8 V |
| • at DC rated value | 6 ... 8 V |
| Supply voltage | |
| Type of voltage of the supply voltage | |
| • of the light source | AC/DC |
| Supply voltage of the light source at AC | |
| • at 60 Hz rated value | 8 ... 6 V |
| Supply voltage of the light source at DC | |
| • rated value | 8 ... 6 V |
| Connections/ Terminals | |
| Type of electrical connection | screw-type terminals |
| • of modules and accessories | Screw-type terminal |
| Tightening torque of the screws in the bracket | 20 N·m |
| Tightening torque [lbf·in] | |
| • with screw-type terminals | 8 ... 8 lbf·in |
| Lamp | |
| Type of light source | filament lamp |
| Color of the light source | clear |
| Safety related data | |
| Protection against electrical shock | finger-safe |
| Ambient conditions | |
| Ambient temperature | |

- during operation
- during storage

-35 ... +70 °C

-40 ... +85 °C

Installation/ mounting/ dimensions

Shape of the installation opening

round

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP3BZ>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP3BZ>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3BZ>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3BZ&lang=en

last modified:

12/04/2019