





fan for 3RW55 and 3RW52 size 4





Product designation	Fans
Manufacturer's article number	
• of soft starter	3RW514 (1x)
• of soft starter	3RW524 (1x)
• of soft starter	3RW554 (1x)
Ambient conditions	
Ambient temperature	
• during storage	-40 ... +80 °C
Certificates/ approvals	

General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping
 CCC	 EAC	 EG-Konf.	 ABS

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

Marine / Shipping	other
 LRS	 PRS



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5984-0FF00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5984-0FF00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5984-0FF00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5984-0FF00&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5984-0FF00/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5984-0FF00&objecttype=14&gridview=view1>

last modified:

02/01/2020