

# SIEMENS

## Data sheet for SIMOTICS M-1PH1



Figure similar

MLFB-Ordering data

1PH1103-1LD12-1GA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Engineering data

Rated power	3.7 kW
Rated speed	1000 rpm
Rated torque	35.0 Nm
Rated current	12.9 A
Rated voltage	269 V
Maximum speed	6000 rpm
Maximum current	25.8 A
Power for duty type S6-25%, maximum	5.55 kW
Standstill torque for duty type S6-25%, maximum	52.5 Nm
Standstill current for duty type S6-25%, maximum	19.0 A
Field weakening speed, max.	4600 rpm
Supply voltage, max.	355 V
Line frequency	36.9 Hz

### Ambient conditions

#### Ambient temperature

Operation	-15 ... 40 °C
Storage	-20 ... 65 °C

#### Relative humidity

Max. operation	90 %
Bearing, max.	95 %

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced-air cooling via fan
Vibration severity grade	Grade B
Degree of protection	IP54
Design acc. to Code I	IM B5 / IM V1
Color	Anthracite 614 / ~ RAL7016
Shaft extension	Feather key with full key balancing
Sound pressure level (1m)	72 dB
Thermal class	F
Mounting type	Flange (round)
Encoder system	Incremental encoder, TTL 2500 ppr (13 bit)