

Solid-state contactor 1-phase 3RF2 AC 15 / 6 A / 40 °C 48-460 V /  
24 V DC Instantaneous switching



<b>Product brand name</b>	SIRIUS
<b>Product designation</b>	solid-state contactor
<b>Product type designation</b>	3RF23
<b>Manufacturer's article number</b>	<ul style="list-style-type: none"> <li>• _1 / of the accessories that can be ordered <a href="#">3RF2900-3PA88</a></li> <li>• _2 / of the accessories that can be ordered <a href="#">3RF2920-0HA16</a></li> <li>• _3 / of the accessories that can be ordered <a href="#">3RF2900-0EA18</a></li> <li>• _4 / of the accessories that can be ordered <a href="#">3RF2920-0GA16</a></li> <li>• _5 / of the accessories that can be ordered <a href="#">3RF2920-0FA08</a></li> </ul>
<b>Product designation</b>	<ul style="list-style-type: none"> <li>• _1 / of the accessories that can be ordered terminal cover</li> <li>• _2 / of the accessories that can be ordered power regulator</li> <li>• _3 / of the accessories that can be ordered converter</li> <li>• _4 / of the accessories that can be ordered load monitoring</li> <li>• _5 / of the accessories that can be ordered load monitoring, basis</li> </ul>
<b>General technical data</b>	
<b>Product function</b>	instantaneous switching
Power loss [W] / for rated value of the current / at AC / in hot operating state	11 W

<b>Insulation voltage</b>	
• rated value	600 V
<b>Degree of pollution</b>	3
<b>Protection class IP</b>	IP20
Shock resistance / acc. to IEC 60068-2-27	15g / 11 ms
Vibration resistance / acc. to IEC 60068-2-6	2g
<b>Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750</b>	K
<b>Reference code / acc. to DIN EN 81346-2</b>	Q
<b>Reference code / acc. to DIN EN 61346-2</b>	Q

### Main circuit

<b>Number of poles / for main current circuit</b>	1
<b>Number of NO contacts / for main contacts</b>	1
<b>Number of NC contacts / for main contacts</b>	0
<b>Operating voltage / at AC</b>	
• at 50 Hz / rated value	48 ... 460 V
• at 60 Hz / rated value	48 ... 460 V
<b>Operating frequency / rated value</b>	50 ... 60 Hz
<b>Operating range relative to the operating voltage / at AC</b>	
• at 50 Hz	40 ... 506 V
• at 60 Hz	40 ... 506 V
<b>Operating current</b>	
• at AC-51 / rated value	10.5 A
<b>Operating current / minimum</b>	100 mA
<b>Rate of voltage rise / at the thyristor / for main contacts / maximum permissible</b>	500 V/ $\mu$ s
<b>Blocking voltage / at the thyristor / for main contacts / maximum permissible</b>	1 200 V
<b>Reverse current / of the thyristor</b>	10 mA
<b>Derating temperature</b>	40 °C
<b>Surge current resistance / rated value</b>	200 A
<b>I<sup>2</sup>t value / maximum</b>	200 A <sup>2</sup> ·s

### Control circuit/ Control

<b>Type of voltage / of the control supply voltage</b>	DC
<b>Control supply voltage / 1</b>	
• at DC / rated value	30 V
• at DC	15 ... 24 V
<b>Control supply voltage</b>	
• at DC / initial value for signal <1> detection	15 V
• at DC / Full-scale value for signal <0> recognition	5 V
<b>Control current / at minimum control supply voltage</b>	

• at DC	13 mA
Control current / at DC / rated value	15 mA
<b>Switch-on delay time</b>	1 ms
<b>Off-delay time</b>	1 ms; additionally max. one half-wave
<b>Number of NC contacts / for auxiliary contacts</b>	0
<b>Number of NO contacts / for auxiliary contacts</b>	0
Number of CO contacts / for auxiliary contacts	0

#### Installation/ mounting/ dimensions

<b>Mounting type</b>	screw and snap-on mounting onto 35 mm standard mounting rail
• Side-by-side mounting	Yes
<b>Height</b>	100 mm
<b>Width</b>	22.5 mm
<b>Depth</b>	91 mm; 94.0 mm up to product revision E05
<b>Installation altitude / at height above sea level / maximum</b>	1 000 m

#### Connections/ Terminals

<b>Type of connectable conductor cross-sections</b>	
• for main contacts	
— solid	2x (1.5 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> )
— finely stranded / with core end processing	2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), 1x 10 mm <sup>2</sup>
• at AWG conductors / for main contacts	2x (14 ... 10)
<b>Type of connectable conductor cross-sections</b>	
• for auxiliary and control contacts	
— solid	1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.0 mm <sup>2</sup> )
— finely stranded / with core end processing	1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.0 mm <sup>2</sup> )
— finely stranded / without core end processing	1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.0 mm <sup>2</sup> )
• at AWG conductors / for auxiliary and control contacts	1x (AWG 20 ... 12)
<b>Tightening torque</b>	
• for main contacts / with screw-type terminals	2 ... 2.5 N·m
• for auxiliary and control contacts / with screw-type terminals	0.5 ... 0.6 N·m
<b>Tightening torque [lbf·in]</b>	
• for main contacts / with screw-type terminals	18 ... 22 lbf·in
• for auxiliary and control contacts / with screw-type terminals	4.5 ... 5.3 lbf·in
<b>Design of the thread / of the connection screw</b>	
• for main contacts	M4
• of the auxiliary and control contacts	M3
<b>Wire stripping length / of the cable</b>	
• for main contacts	7 mm

- for auxiliary and control contacts

7 mm

## Ambient conditions

### Ambient temperature

- during operation
- during storage

-25 ... +60 °C

-55 ... +80 °C

## Electromagnetic compatibility

### Conducted interference

- due to burst / acc. to IEC 61000-4-4
- due to conductor-earth surge / acc. to IEC 61000-4-5
- due to conductor-conductor surge / acc. to IEC 61000-4-5
- due to high-frequency radiation / acc. to IEC 61000-4-6

2 kV / 5 kHz behavior criterion 2

2 kV behavior criterion 2

1 kV behavior criterion 2

140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1

### Electrostatic discharge / acc. to IEC 61000-4-2

4 kV contact discharging / 8 kV air discharging, behavior criterion 2

### Conducted HF-interference emissions / acc. to CISPR11

Class A for industrial environment

### Field-bound HF-interference emission / acc. to CISPR11

Class B for the domestic, business and commercial environments

## Short-circuit protection, design of the fuse link

### Manufacturer's article number

- of gS fuse for semiconductor protection / at NH design
- of full range R fuse link for semiconductor protection / at cylindrical design
- of back-up R fuse link for semiconductor protection / at NH design
- of back-up R fuse link for semiconductor protection / at cylindrical design 10 x 38 mm
- of back-up R fuse link for semiconductor protection / at cylindrical design 14 x 51 mm
- of back-up R fuse link for semiconductor protection / at cylindrical design 22 x 58 mm

[3NE1813-0](#)

[5SE1316](#)

[3NE8015-1](#)

[3NC1016](#)

[3NC1420](#)

[3NC2220](#)

### Manufacturer's article number / of the gG fuse

- at NH design
- at cylindrical design 10 x 38 mm
- at cylindrical design 14 x 51 mm

[3NA6801](#)

[3NW6001-1; These fuses have a smaller rated current than the semiconductor relays](#)

[3NW6101-1; These fuses have a smaller rated current than the semiconductor relays](#)

### Manufacturer's article number

- of DIAZED fuse
- of NEOZED fuse

[5SB141](#)

[5SE2306; These fuses have a smaller rated current than the semiconductor relays](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RF2310-1BA04>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RF2310-1BA04>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2310-1BA04>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3RF2310-1BA04&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3RF2310-1BA04&lang=en)





