

Control Power Transformer, 50va, PRI 230/460v, SEC 24v, Mars Only,

Product brand name	Control Power Transformer
Design of the product	Control power voltage
Special product feature	Complete kit

General technical data

Weight [lb]	3.5 lb
Height x Width x Depth [in]	3.46 × 3 × 3.55 in
Ambient temperature [°F]	
<ul style="list-style-type: none"> during operation maximum 	104 °F
Ambient temperature	
<ul style="list-style-type: none"> during operation maximum 	40 °C
Country of origin	Mexico
Operating apparent output rated value	45 V·A

Enclosure

Design of the housing	Open
-----------------------	------

Mounting/wiring

Mounting position	Any
Mounting type	Surface mounting
Type of electrical connection at output for main current circuit	Screw-type terminals (touchsafe)
Type of electrical connection at input for main current circuit	Screw-type terminals (touchsafe)

Inputs/ Outputs

Input dimensions of primary voltage	240/480vac
Output dimensions of secondary voltage	24vac
Phase number of the inputs	1
Electrical input frequency	50 ... 60 Hz
Input voltage _1	240 V
Input voltage _2	480 V
Phase number of the outputs	1
Electrical output frequency	60 ... 50 Hz
Output voltage _1 rated value	24 V
Certificate of suitability	UL / CSA

Further information

Industrial Controls - Product Overview (Catalogs, Brochures,...)

www.usa.siemens.com/iccatalog

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:KT4050X637>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/US/en/ps/US2:KT4050X637>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:KT4050X637&lang=en

Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/US2:KT4050X637/certificate>

last modified:

11/15/2019