

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7084-5AH71-1DG4-Z
N05



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact
Rated torque (100 K)	9.5 Nm	Shaft height	80 mm
Rated current	7.8 A	Cooling	Natural cooling
Static torque (60 K)	16.80 Nm	Radial runout tolerance	N
Static torque (100 K)	20.0 Nm	Vibration severity grade	Grade R
Stall current (60 K)	13.4 A	Degree of protection	IP65
Stall current (100 K)	15.6 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0045100 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	93.0 %	Color of the housing	
Physical constants		Holding brake version	no value
Torque constant	1.25 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	79.5 V/1000*min ⁻¹	Sensor design	Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits
Winding resistance at 20° C	0.17 Ω	Electrical connectors	Connector turnable
Rotating field inductance	2.9 mH	Connector size	1.5
Electrical time constant	17.00 ms		
Mechanical time constant	1.50 ms		
Thermal time constant	55 min		
Shaft torsional stiffness	65000 Nm/rad		
Net weight of the motor	20.8 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data **1FT7084-5AH71-1DG4-Z**
 N05




Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	4000 rpm	Rated inverter current	18 A
Optimum power	4.8 kW	Maximum inverter current	54 A
Limiting data		Maximum torque	60.00 Nm
Max. permissible speed (mech.)	8000 rpm	Special design	
Max. permissible speed (inverter)	7200 rpm	N05	Non-standard shaft extension (dimensions as for 1FT5 motors)
Maximum torque	81.0 Nm		
Maximum current	80.0 A		