

SITOR fuse link, with blade contacts, NH3, In: 630 A, gS, Un AC: 690 V, Un DC: 440 V, Front indicator



Figure similar

Model	
product brandname	SETRON
Design of an identification indicator	front indicator
Design of the fuse link	SITOR, LV HRC design
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH3
Operating class of the fuse link	gS
circuit-breaker / Design	3NE
Varying load factor (WL)	1
Supply voltage / at DC	440 V
Switching capacity	
Switching capacity current	
• acc. to IEC 60947-2 / rated value	100 kA
Dissipation	
Power loss [W]	

- for rated value of the current / at AC / in hot operating state / per pole
- maximum

55 W

55 W

Electricity

rated current I_n / IEC, DIN/VDE / at 40 °C

630 A

Current / at AC / rated value

630 A

Mechanical Design

Mounting position

Any, preferably vertical

Environmental conditions

Ambient temperature

- minimum
- maximum

-20 °C

50 °C

Environmental category

-20 to +50 at 95% relative humidity

Certificates

Equipment marking

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

F

F

General Product Approval

Declaration of
Conformity

other


[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NE1436-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NE1436-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1436-0

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>




Figure similar