







circular conduc. terminal TA2.3 2 x 4 AWG...300 kcmil for 2 cables; 4 units
accessory for: 3VA61/62

Model	
product brand name	SENTRON
product designation	circular conductor terminal
accessories	Wire connector
General technical data	
designation / of the terminal	TA2.3
type of electrical connection / with control wire tap	No
Connections according IEC	
connectable conductor cross-section	
<ul style="list-style-type: none"> for copper cable / stranded / minimum 	25 mm ²
<ul style="list-style-type: none"> for copper cable / stranded / maximum 	150 mm ²
<ul style="list-style-type: none"> for aluminum cable / stranded / minimum 	25 mm ²
<ul style="list-style-type: none"> for aluminum cable / stranded / maximum 	150 mm ²
stripped length	26 / 51 mm
tightening torque / when using copper cables	
<ul style="list-style-type: none"> stranded 	25 - 150 mm ² : 31.1 Nm
<ul style="list-style-type: none"> finely stranded 	25 - 150 mm ² : 31.1 Nm
Connections according UL	
permissible temperature / of connectable conductor / according to UL 486A-486B	75 °C
stripped length	1.0 / 2.0 in
connectable conductor cross-section	
<ul style="list-style-type: none"> for copper cable / stranded / minimum 	4 AWG
<ul style="list-style-type: none"> for copper cable / stranded / maximum 	300 kcmil
<ul style="list-style-type: none"> for aluminum cable / stranded / minimum 	4 AWG
<ul style="list-style-type: none"> for aluminum cable / stranded / maximum 	300 kcmil
tightening torque / when using copper cables	
<ul style="list-style-type: none"> stranded 	4 AWG - 300 kcmil: 275 lb-in
Certificates	
General Product Approval	Test Certificates
Confirmation    	Type Test Certificates/Test Report
other	Environment



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9244-0JJ22>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9244-0JJ22>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9244-0JJ22

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

8/9/2024

