

INDICATOR LIGHT, 22MM, ROUND, METAL, GREEN, LENS, CONCENTRIC RINGS, WITH HOLDER, LAMPHOLDER, WITH INTEGRATED LED AC 110V, SPRING-LOADED CONNECTION



Figure similar

<b>Design of the product</b>	Complete unit round
<b>Enclosure:</b>	
Shape of the enclosure front	round
Material of the enclosure	metal
Number of command points	0
<b>Actuator:</b>	
Design of the operating mechanism	indicator light
Product extension optional Light source	Yes
Color	
• of the actuating element	Green
Shape of the actuating element	Concentric rings
Type of unlocking device	without
Number of switching positions	0
<b>Front ring:</b>	
Product component front ring	No
<b>Holder:</b>	
Material of the holder	Metal

Contact block/ lampholder:	
Mounting type	integrated LED
Number of lampholders	1
Number of switching elements	0

General technical data:	
Product function	
<ul style="list-style-type: none"> <li>positive opening</li> </ul>	No
Product component	
<ul style="list-style-type: none"> <li>Light source</li> </ul>	Yes
Protection class IP	IP67
Vibration resistance	
<ul style="list-style-type: none"> <li>acc. to IEC 60068-2-6</li> </ul>	20 ... 200 Hz: 5g
Equipment marking	
<ul style="list-style-type: none"> <li>acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750</li> </ul>	H
<ul style="list-style-type: none"> <li>acc. to DIN EN 61346-2</li> </ul>	P
<ul style="list-style-type: none"> <li>acc. to DIN EN 81346-2</li> </ul>	P

Supply voltage:	
Type of voltage of the supply voltage	
<ul style="list-style-type: none"> <li>of the light source</li> </ul>	AC
Supply voltage 1 of the light source at AC	
<ul style="list-style-type: none"> <li>at 50 Hz rated value</li> </ul>	110 V
<ul style="list-style-type: none"> <li>at 60 Hz rated value</li> </ul>	110 V

Auxiliary circuit:	
Number of NC contacts	
<ul style="list-style-type: none"> <li>for auxiliary contacts</li> </ul>	0
Number of NO contacts	
<ul style="list-style-type: none"> <li>for auxiliary contacts</li> </ul>	0
Number of CO contacts	
<ul style="list-style-type: none"> <li>for auxiliary contacts</li> </ul>	0
Consumed current for rated value of supply voltage maximum	15 mA

Connections/ Terminals:	
Type of electrical connection	spring-loaded terminals
Tightening torque of the screws in the bracket	1 N·m

Ambient conditions:	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-25 ... +70 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +80 °C
Environmental category during operation acc. to IEC 60721	3K6

### Installation/ mounting/ dimensions:






Mounting type	front mounting
Shape of the installation opening	round
Mounting diameter	22 mm

### Accessories:

Product component holder for 3 switching elements	No
---	----

### Certificates/approvals

General Product Approval	Declaration of Conformity	Test Certificates
 CCC	 EAC	 EG-Konf.
 CSA		<a href="#">spezielle Prüfbescheinigung</a> <a href="#">n</a>
 UL		

Shipping Approval	other
 ABS	 RINA
 DNV	<a href="#">Bestätigungen</a>
 LRS	
 PRS	

other
<a href="#">sonstig</a> <a href="#">Umweltbestätigung</a>

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB36486BA400CC0>

#### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB36486BA400CC0>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB36486BA400CC0>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB36486BA400CC0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB36486BA400CC0&lang=en)

last modified:

10.03.2016