



CorePro Plastic (Dimmable) A-Shape Lamps

8.8A19/PER/950/P/E26/DIM 6/1FB T20

Dimmable A-shape lamps that offer over 25,000 hours lifetime. Title 20 listed lamps that can be sold in California and ideal for commercial spaces nationwide.

Product data


General Information		Input Frequency	
Cap-Base	E26 [Single Contact Medium Screw]	Input Frequency	60 Hz
Nominal lifetime	15,000 hour(s)	Power Consumption	8.8 W
Switching Cycle	50,000	Lamp Current (Nom)	80 mA
Lighting Technology	LED	Wattage Equivalent	60 W
EU RoHS compliant	Yes	Starting Time (Nom)	0.5 s
		Warm-up time to 60% light	0.5 s
		Power Factor (Fraction)	0.7
		Voltage (Nom)	120 V
Light Technical		Temperature	
Color Code	950 [CCT of 5000K]	T-Case Maximum (Nom)	90 °C
Beam Angle (Nom)	250 degree(s)		
Luminous Flux	800 lm	Controls and Dimming	
Color Designation	Daylight	Dimmable	Yes
Correlated Color Temperature (Nom)	5000 K		
Luminous Efficacy (rated) (Nom)	90.00 lm/W	Mechanical and Housing	
Color Consistency	<4	Bulb Finish	Frosted
Color rendering index (CRI)	90	Bulb Material	Plastic
LLMF At End Of Nominal Lifetime (Nom)	70 %	Bulb Shape	A19 [A 19mm]
Operating and Electrical			
Line Frequency	60 Hz		

CorePro Plastic (Dimmable) A-Shape Lamps

UL Wet/ damp/ dry location	Damp location
Approval and Application	
Energy Consumption kWh/1000 h	- kWh
Energy Certifications	Energy Star
T20 compliant	Yes
Application Conditions	
can it be used in closed luminaires	Yes
Product Data	
Order product name	8.8A19/PER/950/P/E26/DIM 6/1FB T20



Full product name	8.8A19/PER/950/P/E26/DIM 6/1FB T20
Order code	929002036304
Material Nr. (12NC)	929002036304
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677550455
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677550450

Dimensional drawing



Product	D	C
8.8A19/PER/950/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm

Photometric data




Light Distribution Diagram - 8.8A19/PER/950/P/E26/DIM 6/1FB T20

General uniform lighting - 8.8A19/PER/950/P/E26/DIM 6/1FB T20


CorePro Plastic (Dimmable) A-Shape Lamps

Photometric data




Spectral Power Distribution Colour - 8.8A19/PER/950/P/E26/DIM 6/1FB T20

Lifetime



Life Expectancy Diagram - 8.8A19/PER/950/P/E26/DIM 6/1FB T20



Lumen Maintenance Diagram - 8.8A19/PER/950/P/E26/DIM 6/1FB T20

