

Three Pole, Three Phase AC Manual Motor Controller, suitable as Motor Disconnect - 10KA @ 600VAC, 30A max. Class J Fuse.



Features & Benefits

High Horsepower rating of 20HP

Gull-wing shaped brass terminal pressure clamps

Constructed of glass-reinforced thermoplastic

UL508 and cULus Listing of individual device and assembled device within enclosure

Heavy-duty zinc-plated steel strap, two brass rivets secure strap to housing

Two-point contact arm design reduces overall unit size

Two oversized silver alloy contacts withstand years of use; improve heat dissipation by distributing arc energy

One-piece contact carrier constructed of glassreinforced thermoplastic ensures long-lasting ""make and break"" performance

Specifications

General Info

Product Line	Pass & Seymour	UPC Number	785007267686
Country Of Origin	Mexico	Standard	CSA Listed, UL Listed
Type	Manual Controller		

Dimensions

Product Width US	1.825 in	Product Depth US	1.753 in
Product Height US	3.67 in		

Listing Agencies / 3rd Party Agencies

cULus Listed	Yes
--------------	-----

Technical Information

Operating Cycles	50000	Connection	Side & Back Wired
Amperage	30 A	Number of Poles	3 Pole
Wire Size	#14 - #10 AWG	Number of Phases	3
Voltage	600.0 V	Environmental Conditions	UL94 V2
