



Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Selector switch operators

Selection and ordering data

Version	Lever type	Color of lever insert	Cam Code ²⁾	Input Voltage	Order no.	Weight approx. lbs.	Pack unit			
Selector Switches with 2 switching positions										
	Maintained operation	Non-Illuminated, short lever	White	A	52SA2AAB	1				
		Non-Illuminated, long lever	White	A	52SB2AAB					
		Illuminated, short lever ¹⁾ with full voltage 24V, 755 type lamp		A	24V	52SA7ADN	1			
		Illuminated, short lever ¹⁾ with 50/60 Hz transformer 6V, 755 type lamp		A	120V	52SA7AGN	1			
				A	240V	52SA7AHN				
Spring return from right operation	Non-Illuminated, short lever	White	A		52SA2ACB	1				
	Non-Illuminated, long lever	White	A		52SB2ACB					
Selector Switches with 3 switching positions										
	Maintained operation	Non-Illuminated, short lever	White	B	52SA2BAB	1				
		Non-Illuminated, long lever	White	B	52SB2BAB					
		Non-Illuminated, short lever	White	C ³⁾	52SA2CAB					
		Non-Illuminated, long lever	White	C ³⁾	52SB2CAB					
		Non-Illuminated, short lever	White	D	52SA2DAB					
		Non-Illuminated, long lever	White	D	52SB2DAB					
		Non-Illuminated, short lever	White	E	52SA2EAB					
		Non-Illuminated, long lever	White	E	52SB2EAB					
		Non-Illuminated, short lever	White	G	52SA2GAB					
		Non-Illuminated, long lever	White	G	52SB2GAB					
		Illuminated, short lever ¹⁾ with full voltage 24V, 755 type lamp		B	24V			52SA7BDN	1	
				C ³⁾	24V			52SA7CDN		
		Illuminated, short lever ¹⁾ with 50/60 Hz transformer 6V, 755 type lamp		B	120V			52SA7BGN	1	
				C ³⁾	120V			52SA7CGN		
				B	240V			52SA7BHN		
			C ³⁾	240V	52SA7CHN					
Spring return from right operation	Non-Illuminated, short lever	White	B		52SA2BCB	1				
	Non-Illuminated, long lever	White	B		52SB2BCB					
	Non-Illuminated, short lever	White	C ³⁾		52SA2CCB					
	Non-Illuminated, long lever	White	C ³⁾		52SB2CCB					
	Non-Illuminated, short lever	White	D		52SA2DCB					
	Non-Illuminated, long lever	White	D		52SB2DCB					
	Non-Illuminated, short lever	White	E		52SA2ECB					
	Non-Illuminated, long lever	White	E		52SB2ECB					
	Non-Illuminated, short lever	White	G		52SA2GCB					
	Non-Illuminated, long lever	White	G		52SB2GCB					
	Spring return from left operation	Non-Illuminated, short lever	White	B				52SA2BBB	1	
		Non-Illuminated, long lever	White	B				52SB2BBB		
Non-Illuminated, short lever		White	C ³⁾		52SA2CBB					
Non-Illuminated, long lever		White	C ³⁾		52SB2CBB					
Non-Illuminated, short lever		White	D		52SA2DBB					
Non-Illuminated, long lever		White	D		52SB2DBB					
Non-Illuminated, short lever		White	E		52SA2EBB					
Non-Illuminated, long lever		White	E		52SB2EBB					
Non-Illuminated, short lever		White	G		52SA2GBB					
Non-Illuminated, long lever		White	G		52SB2GBB					
Spring return from left and right operation		Non-Illuminated, short lever	White	B		52SA2BDB	1			
		Non-Illuminated, long lever	White	B		52SB2BDB				
	Non-Illuminated, short lever	White	C ³⁾		52SA2CDB					
	Non-Illuminated, long lever	White	C ³⁾		52SB2CDB					
	Non-Illuminated, short lever	White	D		52SA2DDB					
	Non-Illuminated, long lever	White	D		52SB2DDB					
	Non-Illuminated, short lever	White	E		52SA2EDB					
	Non-Illuminated, long lever	White	E		52SB2EDB					
	Non-Illuminated, short lever	White	G		52SA2GDB					
	Non-Illuminated, long lever	White	G		52SB2GDB					
	Selector Switches with 4 switching positions									
	Maintained operation	Non-Illuminated, short lever	White	H		52SA2HAB			1	
Non-Illuminated, long lever		White	H		52SB2HAB					

1) Illuminated selector switches are provided without lenses. Lens kit must be ordered separately on page 10/126.

2) For contact operation, see cam selection chart on page 10/123.

3) The C cam is limited to 4 contact blocks, 1 or 2 pole.