



SIMATIC DP, Connection block M12, 7/8" for ET 200ECO, 2x M12 and 2x 7/8", 2 rotary coding switches for PROFIBUS DP, Address setting

Figure similar

Power loss	
Power loss, typ.	2 W; The power loss depends on the current that you loop through via the connection block.
Dimensions	
Width	79 mm
Height	60 mm
Depth	29 mm
Weights	
Weight, approx.	392 g
Classifications	

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)



[KC](#)



EMV	Maritime application
-----	----------------------



RCM



ABS



BUREAU
VERITAS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)

Maritime application



RINA

[CCS \(China Classification Society\)](#)



KR
KOREAN REGISTER

last modified:

4/4/2025