

Connection element, for round cable, for routing the round cable into the enclosure, for AS-i enclosure, plastic and metal, with 4-6 control points, M25,

product designation	connection element		
<b>General technical data</b>			
reference code according to IEC 81346-2	X		
Substance Prohibitance (Date)	07/01/2006		
Weight	0.03 kg		
<b>Ambient conditions</b>			
ambient temperature during operation	-25 ... +70 °C		
<b>Installation/ mounting/ dimensions</b>			
fastening method	direct mounting		
<b>Approvals Certificates</b>			
General Product Approval	other	Environment	Industrial Communication



[Confirmation](#)

[Environmental Confirmations](#)



### Further information

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SF5900-0CK>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SF5900-0CK>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5900-0CK>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SF5900-0CK&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SF5900-0CK&lang=en)

last modified:

4/2/2025