

Data sheet for SIMOTICS S-1FK7

No image available for this configuration.

MLFB-Ordering data

1FK7044-7AF71-1EH2

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data | |
|-----------------------|-------------------------|
| Rated speed (100 K) | 3000 rpm |
| Number of poles | 6 |
| Rated torque (100 K) | 3.5 Nm |
| Rated current | 4.0 A |
| Static torque (60 K) | 3.00 Nm |
| Static torque (100 K) | 4.0 Nm |
| Stall current (60 K) | 3.40 A |
| Stall current (100 K) | 4.50 A |
| Moment of inertia | 1.410 kgcm ² |
| Efficiency | 91.0 % |

| Physical constants | |
|-----------------------------|-------------------------------|
| Torque constant | 0.86 Nm/A |
| Voltage constant at 20° C | 57.0 V/1000*min ⁻¹ |
| Winding resistance at 20° C | 1.50 Ω |
| Rotating field inductance | 20.0 mH |
| Electrical time constant | 13.30 ms |
| Mechanical time constant | 0.78 ms |
| Thermal time constant | 45 min |
| Shaft torsional stiffness | 9500 Nm/rad |
| Net weight of the motor | 8.3 kg |

| Mechanical data | |
|--------------------------|---|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | High Dynamic |
| Shaft height | 48 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.08 mm |
| Axial runout tolerance | 0.08 mm |
| Vibration severity grade | Grade A |
| Connector size | 1 |
| Degree of protection | IP65 and DE flange IP67 |
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Temperature monitoring | KTY84 temperature sensor in the stator winding |
| Electrical connectors | Connectors for signals and power rotatable |
| Color of the housing | without |
| Holding brake | with holding brake |
| Shaft extension | Plain shaft |
| Encoder system | Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface |

MLFB-Ordering data

1FK7044-7AF71-1EH2

Figure similar

Optimum operating point

| | |
|---------------|----------|
| Optimum speed | 3000 rpm |
| Optimum power | 1.1 kW |

Limiting data

| | |
|-----------------------------------|-----------|
| Max. permissible speed (mech.) | 8000 rpm |
| Max. permissible speed (inverter) | 10100 rpm |
| Maximum torque | 12.0 Nm |
| Maximum current | 14.8 A |

Holding brake

| | |
|-----------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 4.0 Nm |
| Power supply voltage | DC 24 V \pm 10 % |
| Coil current | 0.5 A |
| Opening time | 70 ms |
| Closing time | 30 ms |
| Highest braking work | 150 J |

Recommended Motor Module

| | |
|--------------------------|---------|
| Rated inverter current | 5 A |
| Maximum inverter current | 10 A |
| Maximum torque | 8.80 Nm |