

Enabling module for operator panel 3RA69350A

General technical data		
product brand name		SIRIUS
product designation		dongle
protection class IP on the front according to IEC 60529		IP20
touch protection on the front according to IEC 60529		Finger-safe, for vertical contact
relative humidity during operation	%	10 ... 90
ambient temperature		
• during transport	°C	-55 ... +80
• during storage	°C	-55 ... +80
• during operation	°C	-20 ... +60
reference code according to EN 61346-2		T
Installation/ mounting/ dimensions		
width	mm	18
height	mm	16
depth	mm	10
Certificates/ approvals		
certificate of suitability		IEC / EN 60947-6-2
General Product Approval		EMV



EG-Konf.






[Confirmation](#)



UL



RCM

Marine / Shipping	other	Environment
 <p>ABS</p>  <p>DNV</p>  <p>PRS</p>	<p>Confirmation</p>	<p>Environmental Confirmations</p>

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA6936-0A>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6936-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA6936-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6936-0A&lang=en

last modified:

3/11/2024