

\*\*\*No longer available\*\*\* SIMATIC Field PG M5 Advanced; I7-6820EQ (2.8 to 3.5 GHz; 4 kernels+hyperthreading; 8 MB SMART cache); 15.6" display; Full HD (1920x 1080); WLAN 802.11AC & Bluetooth V4.0; DVD +/-RW; HD graphic 530 1x 16 GB DDR4 SD-RAM SO-DIMM 512 GB SSD SATA (2.5"); without S5 interface, without S5-EPROMMER Line cable with power plug: USA; Keyboard: QWERTZ/QWERTY Windows 7 Ultimate SP1, 64 bit License for STEP 7 Prof combo (V15 & 2017), WinCC Advanced combo (V15 & WinCC flexible 2008) Version of the software V14.0.1.1

General information	
Design of the programming device	Notebook
Display	
Design of display	15.6" full HD display in 16:9 format
Resolution (pixels)	
• Horizontal image resolution	1 920 Pixel
• Vertical image resolution	1 080 Pixel
General features	
• Non-reflecting	Yes
• Luminance	300 cd/m <sup>2</sup>
Backlighting	
• Type of backlighting	LED
Control elements	
Keyboard fonts	
• Design	QWERTZ/QWERTY or AZERTY (French); 87 keys
Touch operation	
• Integrated touch pad	Yes; Clickpad
Supply voltage	
Design of the power supply	External wide-range power supply; 3-pole
permissible range, lower limit (AC)	100 V; ±10 %, sinusoidal
permissible range, upper limit (AC)	240 V; ±10 %, sinusoidal
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Processor	
Processor type	Intel Core i5-6440EQ (2.7 GHz to 3.4 GHz, 4 cores, 6 MB Smart Cache) or i7-6820EQ (2.8 GHz to 3.5 GHz, 4 cores, 8 MB Smart Cache)
Chipset	Mobile Intel QM170

Hyper-threading	Yes; for Intel Core i7 processor
Turbo Boost Technology 2.0	Yes
<b>Graphic</b>	
Graphics controller	Intel® HD graphics 530
<b>Drives</b>	
DVD-RW	Yes
Hard disk	Yes; Easy to replace
• Memory capacity	1 Tbyte; HDD
SSD	Yes; Easy to replace
• Memory capacity	512 Gbyte
TPM Security Chip	Yes; 2.0 (version for China without TPM)
<b>Memory</b>	
Type of memory	DDR4-SDRAM SO-DIMM
<b>Work memory</b>	
• Number of slots	2; Can be equipped with 1x 8 GB, 1x 16 GB or 2x 16 GB
<b>Accumulator</b>	
Replaceable	Yes; Lithium-ion battery
Capacity	8.8 A·h
<b>Hardware configuration</b>	
<b>Slots</b>	
• Number of ExpressCard slots	1; Type 34
<b>Interfaces</b>	
Number of interfaces PROFIBUS DP	1
Number of RS 232 interfaces	1; 25-pin socket
Number of USB interfaces	4; USB 3.0
• Type A	3; 1x USB port incl. integrated charging function for USB devices (e.g. smartphone) - also with device switched off
• Type C	1
Number of chip-card readers	1; Smart Card Reader (ISO/IEC 7816)
Bluetooth radio standard	Yes; V4.0
Multimedia card/SD card slot	2 in 1 (SDHC UHS-II, MMC)
Card reader for SIMATIC memory cards	SIMATIC memory cards (for S7-300/400), SMC (for S7-1x00), SIMATIC micro memory card (for S7-300/C7/ET 200) - including programming interfaces
Universal Audio Jack	Yes; Audio socket for 3.5 mm jack
<b>Video interfaces</b>	
• analog video signal (VGA)	Yes; via adapter from DVI to VGA
• DVI-I	Yes; 1x
• DisplayPort	Yes; 1x
<b>Industrial Ethernet</b>	
• Industrial Ethernet interface	2x Ethernet (RJ45)

— 100 Mbps	Yes
— 1000 Mbps	Yes; Gigabit Ethernet; 2x RJ45 with 2 independent MAC/IP addresses
• Wake on LAN	Yes; Via Port 1
• IAMT (Intel Active Management Technology)	Yes

WLAN	
• Type	802.11ac

## EMC

### Interference immunity against discharge of static electricity

• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes; ±4 kV contact discharge (to IEC 801-2/IEC 1000-4-2; ESD), ±8 kV air discharge (to IEC 801-2/IEC 1000-4-2; ESD)
---	---

### Interference immunity to cable-borne interference

• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables	±1 kV (according to IEC 61000-4-4, burst, length < 30 m); ±2 kV (according to IEC 61000-4-4, burst, length > 30 m); ±2 kV (according to IEC 61000-4-5, surge sym./line to ground, length > 30 m)

## Standards, approvals, certificates

CE mark	Yes
CSA approval	Yes
UL approval	Yes
DIN/ISO 9001	Yes

## Ambient conditions

### Ambient temperature during operation

• min.	5 °C; Max. 10 °C/h (no condensation)
• max.	40 °C; Max. 10 °C/h (no condensation)

### Ambient temperature during storage/transportation

• min.	-20 °C; Max. 20 °C/h (no condensation)
• max.	60 °C; Max. 20 °C/h (no condensation)

### Relative humidity

• Operation, min.	5 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14
• Operation, max.	85 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14

### Vibrations

• Operation, tested according to IEC 60068-2-6	Yes
--	-----

### Shock testing

• tested according to IEC 60068-2-27	Yes
--------------------------------------	-----

## Operating systems

pre-installed operating system	
--------------------------------	--

- Windows 7

Yes; Ultimate 64 bit, SP1

## Software

### Preinstalled

- |                                    |  |
|------------------------------------|--|
| • STEP 7 Professional 2010         | Yes; Software version: SR4   |
| • STEP 7 Professional (TIA Portal) | Yes; Software version: V14   |
| • WinCC flexible Advanced 2008     | Yes; Software version: SP3   |
| • WinCC Advanced (TIA Portal)      | Yes; Software version: V14   |
| • STEP 5                           | Yes; Optional; software version: STEP 5 V7.23 HF2 (incl. GRAPH 5/II V7.15) |

## Mechanics/material

Material of housing	metal
Handle	Yes; retractable
Socket for Kensington lock	Yes
rubber corner guards	Yes

## Dimensions

Width	385 mm
Height	53 mm
Depth	275 mm

## Weights

Weight, approx.	3.4 kg; incl. rechargeable battery
-----------------	------------------------------------

## Scope of supply

Accumulator	Yes
Power supply	Yes
Backpack	Yes
SIMATIC Software	Yes
Recovery media	Yes; Restore & Recovery

## Other

free hotline	Yes
Note:	Made in Germany: development and production in Germany

**last modified:** 02/13/2020