



**Auxiliary contact block 0NO / 2NC**  
**For use on Class CLM 300 and 400 Amp lighting contactors**



Image is representative and may not depict the actual product.

<b>General technical data:</b>	
Weight	.010 lb
Height x Width x Depth	62 x 25 x 35 mm
Finger-safe	No
Maximum altitude	6560 ft
Ambient storage temperature	(-55 to 80)°C / (-67 to 176)°F
Ambient operating temperature	(-35 to 75)°C / (-31 to 167)°F
Humidity (% non-condensing)	(no data)
Rated impulse voltage resistance	(no data)
Rated insulation voltage	(no data)
Country of origin	USA
Number of NC contacts	2
Number of NO contacts	0
<b>Operating Current at A600:</b>	
Continuous current	10A
120 VAC	60A Make / 6A Break
240 VAC	30A Make / 3A Break
480 VAC	15A Make / 1.5A Break
600 VAC	12A Make / 1.2A Break
Voltamperes	7200 Make / 720 Break
<b>Operating Current at R300:</b>	
Continuous current	1.0A
125 VDC	0.22A Make / 0.22A Break
250 VDC	0.11A Make / 0.11A Break
301 to 600 VDC	NA
Voltamperes	28 Make / 28 Break
<b>Mounting/wiring:</b>	
Connection type / torque	Screw / 8 - 12 in-lb
Solid & stranded conductors	2x(12-16 AWG) CU 75°C
<b>Certificates/approvals:</b>	
<b>Additional information:</b>	
<a href="#">Instruction Sheet</a>	

