

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7043-4CF21-1AG2

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	6	Motor type	High Dynamic		
Rated torque (100 K)	3.0 Nm	Shaft height	48		
Rated current	3.7 A	Cooling	Natural cooling		
Static torque (60 K)	2.90 Nm	Radial runout tolerance	0.040 mm		
Static torque (100 K)	3.3 Nm	Concentricity tolerance	0.08 mm		
Stall current (60 K)	3.30 A	Axial runout tolerance	0.08 mm		
Stall current (100 K)	3.90 A	Vibration severity grade	Grade A		
Moment of inertia	1.000 kgcm ²	Connector size	1		
Efficiency	88.0 %	Degree of protection	IP65 and DE flange IP67		
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Temperature monitoring	KTY84 temperature sensor in the stator winding		
		Electrical connectors	Connectors for signals and power rotatable		
		Color of the housing	Standard (Anthracite RAL 7016)		
		Holding brake	without holding brake		
		Shaft extension	Plain shaft		
		Encoder system	Encoder IC2048S/R: incremental encoder sin/cos 1 Vpp 2048 S/R with C and D track		
		Torque constant	0.84 Nm/A		
		Voltage constant at 20° C	54.0 V/1000*min ⁻¹		
		Winding resistance at 20° C	1.20 Ω		
Rotating field inductance	13.6 mH				
Electrical time constant	11.30 ms				
Mechanical time constant	0.50 ms				
Thermal time constant	40 min				
Shaft torsional stiffness	11400 Nm/rad				
Net weight of the motor	6.0 kg				



Figure similar

MLFB-Ordering data

1FK7043-4CF21-1AG2

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	4 A
Optimum power	0.9 kW	Maximum inverter current	8 A
Limiting data		Maximum torque	6.60 Nm
Max. permissible speed (mech.)	9000 rpm		
Max. permissible speed (inverter)	5350 rpm		
Maximum torque	10.0 Nm		
Maximum current	12.5 A		