



Figure similar

MLFB-Ordering data

1FK7040-5AK71-1PB0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data	
Rated speed (100 K)	6000 rpm
Number of poles	8
Rated torque (100 K)	1.1 Nm
Rated current	1.7 A
Static torque (60 K)	1.30 Nm
Static torque (100 K)	1.6 Nm
Stall current (60 K)	1.80 A
Stall current (100 K)	2.25 A
Moment of inertia	2.130 kgcm ²
Efficiency	88.0 %

Physical constants	
Torque constant	0.68 Nm/A
Voltage constant at 20° C	43.0 V/1000*min ⁻¹
Winding resistance at 20° C	3.30 Ω
Rotating field inductance	17.0 mH
Electrical time constant	5.15 ms
Mechanical time constant	3.62 ms
Thermal time constant	25 min
Shaft torsional stiffness	19000 Nm/rad
Net weight of the motor	4.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	with holding brake
Shaft extension	Feather key
Encoder system	Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole)

MLFB-Ordering data

1FK7040-5AK71-1PB0

Figure similar

Optimum operating point

Optimum speed	6000 rpm
Optimum power	0.7 kW

Limiting data

Max. permissible speed (mech.)	9000 rpm
Max. permissible speed (inverter)	9990 rpm
Maximum torque	5.1 Nm
Maximum current	7.7 A

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	4.0 Nm
Power supply voltage	DC 24 V \pm 10 %
Coil current	0.5 A
Opening time	70 ms
Closing time	30 ms
Highest braking work	150 J

Recommended Motor Module

Rated inverter current	3 A
Maximum inverter current	6 A
Maximum torque	4.10 Nm