



3/8" -16NC Tapped Hole for Grounding Both sides of Frame (Rosca para Tierra en ambos lados)

① Tolerancias According to NEMA Std.
 ② All these dimensions corresponding to assemblies and castings shall have a tolerance as per DIN standard 1686-GTB 19.
 ③ Not According to NEMA Std.

CERTIFIED PRINT / CERTIFICACION			
CUSTOMER/CLIENTE	SAW/ORDER COMPANY	TYPE/PRO	REV/ISS
IP	FRANK/ARM	VOLTS	REV

Tol. in mm. acc. to Tol. en mm. según DIN-1686-GTB-19	Over/desde To/hasta
18	± 4.5
30	± 4.7
50	± 5
80	± 5.5
120	± 6
180	± 6.5
250	± 7
315	± 7.5
400	± 8
500	± 8.5
630	± 9.5
800	± 10

European Projection / Proyeccion Europea
 Dim. in inches / Dim. en pulg.

Date/Fecha	Name/Nombre
15/01/09	J. Carvajal
Drawn/Elab.	Check/Rev.
Std/Cnd/Aut	

SIEMENS
 GUADALAJARA FACTORY

3MSE 740 0651

Ref. / Rep. / Sáb. / - / -

Scale / Escala / - / -

NOTE: Changed the type of motor
 NOTA: Se cambio el tipo de motor

Outline / Dimensiones

Type / SD10, SD10 MS, SD100 mNP FRAME/ARM. 404/405T
 Tipo. SD10, SD10 MS, SD100 mNP FRAME/ARM. 404/405T