

SIMATIC IPC277G (nanopanel PC); 15" multi-touch (1920 x 1080); 3x 10/100/1000 Mbps Ethernet RJ45; 2x display port graphic; 4x USB 3.1, 2x M.2 extension slot; 24 V DC industrial power supply Atom X6414RE (4-core) with TPM; 16 GB RAM / without USB flash drive (documentation) without COM; 256 GB Eco SSD; without hardware extension; without software; ;

General information	
Product type designation	IPC277G
Display	
Design of display	15" TFT multi-touch
Screen diagonal	15 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	80 W
Dimensions	
Width of the housing front	398 mm
Height of housing front	257 mm
Mounting cutout, width	382 mm
Mounting cutout, height	241 mm
Overall depth	105 mm
Weights	
Weight, approx.	5.3 kg

Classifications		Version	Classification
eClass		14	19-20-01-03
eClass		12	19-20-01-03
eClass		9.1	19-20-01-03
eClass		9	19-20-01-03
eClass		8	27-24-23-01
eClass		7.1	27-24-23-01
eClass		6	27-24-23-01
ETIM		10	EC001414
ETIM		9	EC001414
ETIM		8	EC001414
ETIM		7	EC001414

Approvals / Certificates	
General Product Approval	



Miscellaneous



KC



last modified:

5/7/2025 