



CIRCUIT-BREAKER VL 250 UL TYPE FG (CAT NO. LFK3B200) NON-INTERCHANGEABLE FRAME W. APPROBATION CIRCUIT-BREAKER ACC. UL489 VERY HIGH BREAKING CAPACITY 3-POLE, NEMA RATING 100KA@480V AND 18KA@600/347V (MOLDED CASE CIRCUIT BREAKER) OVERCURRENT RELEASE TM, LI TU= 40 DEGR. CELSIUS IN=200A, RATED CURRENT II= 1000...2000A SHORT-CIRCUIT PROTECTION IR= 200A OVERCURRENT RELEASE F. PLANT PROTECTION W/O CONNECTION ACCESSORIES

Model	
Type of the driving mechanism / motor drive	No
Design of the overcurrent release	TM
General technical data	
Number of poles	3
Size of the circuit-breaker	3VL3 UL
Electrical endurance (switching cycles) / typical	10 000
Usage category	A
Performance class for circuit breaker	N
Mechanical service life (switching cycles) / typical	20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
Operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage Ue / max.	690 V
Insulation voltage	
• rated value	800 V
• at AC / rated value	800 V

Surge voltage resistance / rated value	8 kV
--	------

### Protection class

<b>Protection class IP</b>	IP20
<b>Protective function of the overcurrent release</b>	LI

### Electricity

Operating current / at 45 °C / rated value	186 A
Continuous current / rated value	200 A
Derating temperature / for the rated value of the continuous current	50 °C
<ul style="list-style-type: none"> <li>• acc. to UL 489</li> </ul>	40 °C
<b>Adjustable pick-up value current</b>	
<ul style="list-style-type: none"> <li>• of the current-dependent overload release / Full-scale value</li> </ul>	200 A
<ul style="list-style-type: none"> <li>• of instantaneous short-circuit trip unit / initial value</li> </ul>	1 000 A
<ul style="list-style-type: none"> <li>• of instantaneous short-circuit trip unit / Full-scale value</li> </ul>	2 000 A

### Main circuit

<b>Operating frequency</b>	
<ul style="list-style-type: none"> <li>• 1 / rated value</li> </ul>	50 Hz
<ul style="list-style-type: none"> <li>• 2 / rated value</li> </ul>	60 Hz
<b>Operating voltage</b>	
<ul style="list-style-type: none"> <li>• rated value / maximum</li> </ul>	690 V
<ul style="list-style-type: none"> <li>• for main current circuit / at AC / at 50 Hz / acc. to UL 489 / maximum</li> </ul>	600 V
<ul style="list-style-type: none"> <li>• for main current circuit / at AC / at 50 Hz / maximum</li> </ul>	690 V
<ul style="list-style-type: none"> <li>• for main current circuit / at AC / at 60 Hz / acc. to UL 489 / maximum</li> </ul>	600 V
<ul style="list-style-type: none"> <li>• for main current circuit / at AC / at 60 Hz / maximum</li> </ul>	690 V
<b>Operating current</b>	
<ul style="list-style-type: none"> <li>• at 40 °C / rated value</li> </ul>	200 A
<ul style="list-style-type: none"> <li>• at 50 °C / rated value</li> </ul>	186 A
<ul style="list-style-type: none"> <li>• at 55 °C / rated value</li> </ul>	172 A
<ul style="list-style-type: none"> <li>• at 60 °C / rated value</li> </ul>	172 A

### Suitability

<b>Suitability for use</b>	system protection
----------------------------	-------------------

### Adjustable parameters

<b>Adjustable pick-up value current / of the current-dependent overload release / initial value</b>	200 A
---	-------

## Product details

<b>Product component</b>	
• Trip indicator	No
• Auxiliary switch	No
• Voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
Product extension / optional / motor drive	Yes

## Product function

<b>Product function</b>	
• of thermal overload trip unit	fixed
• Ground fault protection	No
• for neutral conductors / Short-circuit and overload proof	No
• Overload protection	Yes

## Short circuit

<b>Operational short-circuit current breaking capacity (Ics)</b>	
• at 240 V / rated value	150 kA
<b>Maximum short-circuit current breaking capacity (Icu)</b>	
• at 240 V / rated value	200 kA
• at 480 V / acc. to NEMA / rated value	100 kA

## Connections

Arrangement of electrical connectors / for main current circuit	front side
Type of electrical connection / for main current circuit	without connection accessoires

## Mechanical Design

<b>Height</b>	185.5 mm
<b>Width</b>	104.5 mm
<b>Depth</b>	106.5 mm
<b>Mounting type</b>	fixed mounting

## Environmental conditions

<b>Ambient temperature</b>	
• during operation / minimum	0 °C
• during operation / maximum	70 °C
• during storage / minimum	-40 °C
• during storage / maximum	80 °C

## Certificates

<b>Certificate of suitability</b>	UL very high switching capacity (L), non-interchangeable
<b>Equipment marking</b>	

<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>
---------------------------------	------------	----------------------------------



[Miscellaneous](#)



<b>Test Certificates</b>	<b>Shipping Approval</b>	<b>other</b>		
--------------------------	--------------------------	--------------	--	--

[Special Test Certificate](#)



[Miscellaneous](#)

[Environmental Confirmations](#)

[Confirmation](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3520-3KN30-0AA0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL3520-3KN30-0AA0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL3520-3KN30-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3520-3KN30-0AA0)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>