SIEMENS

Datasheet for SIMOGEAR Geared Motors

21.19

MLFB-Ordering data : **2KJ3508-9HJ23-9GL1-Z**

D16+H06+H6A+K01+K07+L02+L75+M67+N38+N3A+N67+P91

Client order no. :
Order no. :
Offer no. :

Item no. :
Consignment no. :
Project :

Motor data

U [V]	D/Y	f_N [Hz]	P_N [kW]	P_N [hp]	I_N [A]	n_N [rpm]	T_N [Nm]	IE-CL	Operating mode	n_2 [rpm]	T_2 [Nm]	f_B	η [%] 4/4	3/4	2/4	cos φ	I_A/I_N	T_A/T_N	T_K/T_N	T_H/T_N
230	D	50	5.500	7.37	18.80	1,470	35.73	IE3	S1	60.819	863.63	0.89	89.6	90.0	89.4	0.82	8.50	2.90	3.70	3.20
400	Y	50	5.500	7.37	10.80	1,470	35.73	IE3	S1	60.819	863.63	0.89	89.6	90.0	89.4	0.82	8.50	2.90	3.70	3.20
460	Y	60	5.500	7.37	9.30	1,775	29.59	IE3	CONT.	73.438	715.23	1.08	91.7	91.6	90.5	0.81	10.00	3.10	4.20	3.40
400	D	87	9.600	12.87	18.50	2,580	35.53	-	INV.DUTY	106.743	858.88	0.90	91.8	0.0	0.0	0.82	0.00	0.00	3.90	0.00
460	D	104	9.600	12.87	16.30	3,095	29.62	-	INV.DUTY	128.051	715.96	1.08	90.2	0.0	0.0	0.82	0.00	0.00	4.40	0.00

Motor type	1LE motor with Premium Efficiency LE132ZST4P
Number of poles	4-pole
Degree of protection	(K01) IP55
Thermal class	155 (F)
Moment of inertia Jmot	0.03400 kgm²
Terminal box position	(M67) 4A
Electrical connection at terminal box	Cable gland metric
Ventilation	Standard fan

Geared motor

Type designation	SIMOGEAR KG79-LE132ZST4P
Gearbox	Bevel gearbox KG79
Mounting type gearbox	Flange on opp. side
Output shaft	V1.625" x 3.15" (Solid shaft with feather key)
Mounting position	(D16) M6 output side A
Transmission ratio	24.17 (83545 / 3456)
Nominal torque	770.00 Nm
Gear oil	(K07) Synthetic oil CLP PG VG220
Oil charge	2.7 l
Specification	CE (Europe / other countries)
Environment temperature	-15 ... +40 °C
Weight without oil	106.2 kg
Housing material first gearbox	Cast iron

General options

Surface treatments	Painted
Coating	(L02) Coating for normal environmental stress C1
RAL Color	(L75) 7016 anthracite gray
Coating on flange	-
Packing	Standard packing

Further information

General product information	SIMOGEAR
Configurator	2KJ.....
Operating instructions	
Gearbox	BA 2030
Motor	BA 2330
Catalog	MD 50.1 Geared motors

Gearbox options

Flange diameter	(H06) 250 mm
Hollow shaft cover	Sealing cap
Output shaft bearing	Standard bearing
Output shaft sealing	Standard sealing
Gearbox breather	Pressure breather valve
Oil level control	Oil level screw
Oil drain	Oil drain plug

Motor options

Motor protection	Without

Legend

U = Voltage
D / Y = Circuit
f = Frequency
P_N = Rated motor power
I_N = Rated current
n_N = Rated motor speed
T_N = Rated motor torque
IE-CL = Efficiency class
n_2 = Geared motor output speed
T_2 = Geared motor output torque
f_B = Service factor
η = Efficiency
*) On request
cos φ = Power factor
I_A/I_N = Relative starting current
T_A/T_N = Relative starting torque
T_K/T_N = Relative breakdown torque
T_H/T_N = Relative average acceleration torque

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

Generated: 2021-06-14 14:54