



Figure similar

Surge suppressor RC element for snapping on 127-240 V AC / 150-250 V DC for contactors Size 8-12, AC operation Size 3-6, DC operation

<b>product category</b>	Surge suppressor	
<b>product designation</b>	RC element	
<b>Substance Prohibittance (Date)</b>	07/01/2006	
<b>Weight</b>	0.083 kg	
<b>type of voltage of the control supply voltage</b>	AC/DC	
<b>control supply voltage at AC</b>		
• at 50 Hz rated value	127 ... 240 V	
• at 60 Hz rated value	127 ... 240 V	
<b>control supply voltage 1 at AC</b>		
• at 50 Hz	127 ... 240 V	
• at 60 Hz	127 ... 240 V	
<b>control supply voltage frequency</b>		
• 1 rated value	50 Hz	
• 2 rated value	60 Hz	
<b>control supply voltage at DC rated value</b>	150 ... 250 V	
<b>control supply voltage 1 at DC</b>	150 ... 250 V	
<b>design of the surge suppressor</b>	RC element	
<b>Ambient conditions</b>		
<b>ambient temperature</b>		
• during operation	-25 ... +55 °C	
• during storage	-40 ... +80 °C	
<b>Approvals Certificates</b>		
<b>General Product Approval</b>	<b>other</b>	<b>Environment</b>



[Confirmation](#)

[Environmental Confirmations](#)

### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7522-3T>

Cax online generator

<http://support.automation.siemens.com/WWW/CAXorder/default.aspx?lang=en&mlfb=3TX7522-3T>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7522-3T>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3TX7522-3T&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7522-3T&lang=en)

---

last modified:

9/10/2024 