




LED lamp flashing (1.4 Hz), yellow, Rated voltage 24-28 V AC/DC Operating current 40 mA, Base BA 9s, piston diameter 10 mm



General technical data		
Product designation		LED lamp
Type of light source		LED
Color of the light source		yellow
Mounting type		BA 9s
Product component		
• series resistor		No
• diode		No
• lamp transformer		No
• Light source		Yes
Type of voltage for actuation		DC
Operating voltage		
• at DC rated value	V	24 ... 28
Relative positive tolerance of the operating voltage	%	10
Relative negative tolerance of the operating voltage	%	-15
Consumed current for rated value of supply voltage maximum	mA	40
Type of electrical connection		Miscellaneous
Mounting type		miscellaneous

## Certificates/ approvals

General Product Approval	Declaration of Conformity	other	Railway
 UL		 EG-Konf.	<a href="#">Miscellaneous</a> <a href="#">Confirmation</a> <a href="#">Special Test Certificate</a>

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3SB1902-4MC>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3SB1902-4MC>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB1902-4MC>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3SB1902-4MC&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3SB1902-4MC&lang=en)

last modified:

03/06/2020