



Figure similar

MLFB-Ordering data

1FK7100-5AF71-1UU5

Client order no. :
 Order no. :
 Offer no. :
 Remarks :

Item no. :
 Consignment no. :
 Project :

Engineering data	
Rated speed (100 K)	3000 rpm
Number of poles	8
Rated torque (100 K)	12.0 Nm
Rated current	8.0 A
Static torque (60 K)	15.00 Nm
Static torque (100 K)	18.0 Nm
Stall current (60 K)	9.20 A
Stall current (100 K)	11.20 A
Moment of inertia	55.300 kgcm ²
Efficiency	92.0 %

Physical constants	
Torque constant	1.59 Nm/A
Voltage constant at 20° C	101.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.34 Ω
Rotating field inductance	7.0 mH
Electrical time constant	20.50 ms
Mechanical time constant	2.23 ms
Thermal time constant	55 min
Shaft torsional stiffness	184000 Nm/rad
Net weight of the motor	19.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft extension	Fitted key and keyway
Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)

MLFB-Ordering data

1FK7100-5AF71-1UU5

Figure similar

Optimum operating point

Optimum speed 3000 rpm

Optimum power 3.8 kW

Limiting data

Max. permissible speed (mech.) 5000 rpm

Max. permissible speed (inverter) 5700 rpm

Maximum torque 55.0 Nm

Maximum current 37.0 A

Recommended Motor Module

Rated inverter current 18 A

Maximum inverter current 36 A

Maximum torque 53.80 Nm