

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7086-5AC70-1CG3



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	2000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact
Rated torque (100 K)	22.5 Nm	Shaft height	80 mm
Rated current	9.2 A	Cooling	Natural cooling
Static torque (60 K)	23.00 Nm	Radial runout tolerance	N
Static torque (100 K)	28.0 Nm	Vibration severity grade	Grade R
Stall current (60 K)	8.9 A	Degree of protection	IP64
Stall current (100 K)	10.6 A	Design acc. to Code I	IM B5 (new flange design)
Rotor moment of inertia	0.0063600 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	93.0 %	Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Physical constants		Holding brake version	no value
Torque constant	2.59 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	165.0 V/1000*min ⁻¹	Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Winding resistance at 20° C	0.47 Ω	Electrical connectors	Connector turnable
Rotating field inductance	8.5 mH	Connector size	1
Electrical time constant	18.00 ms		
Mechanical time constant	1.30 ms		
Thermal time constant	60 min		
Shaft torsional stiffness	57000 Nm/rad		
Net weight of the motor	27.5 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7086-5AC70-1CG3



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	18 A
Optimum power	4.7 kW	Maximum inverter current	54 A
Limiting data		Maximum torque	120.00 Nm
Max. permissible speed (mech.)	8000 rpm		
Max. permissible speed (inverter)	3500 rpm		
Maximum torque	120.0 Nm		
Maximum current	54.0 A		