



Selector switch, keyed
30 mm
Three position maintained
HAND - OFF - AUTO legend



Image is representative and may not depict the actual product.

General technical data:	
Weight	0.55 lb
Height x Width x Depth	2.1 x 2.0 x 3.94 in (without key)
Finger-safe	Yes
Environmental ratings	NEMA 1, 3, 3R, 4, 12 & 13
Maximum altitude	(no data)
Ambient storage temperature	(-40 to 85)°C / (-40 to 185)°F
Ambient operating temperature	(-35 to 70)°C / (-31 to 158)°F
Humidity (% non-condensing)	(no data)
Country of origin	Mexico
Material of front ring	Metal with chrome plating
Actuator:	
Type	Short lever
Material	Plastic
Illumination	None
Switching positions	3 maintained positions
Key removal	All positions
Mechanical service life (switching cycles)	2,000,000 operating cycles
Contact Block:	
Number of NC contacts	1
Number of NO contacts	1
Operating Current at A600:	
Thermal continuous test circuit	10A
120VAC	60A Make / 6A Break
240VAC	30A Make / 3A Break
480VAC	15A Make / 1.5A Break
600VAC	12A Make / 1.2A Break
Operating Current at P600:	
Thermal continuous test circuit	5A
125VDC	1.1A Make or Break
250VDC	0.55A Make or Break
301 to 600VDC	0.2A Make or Break
Legend:	
Material	Brushed aluminum
Inscription	HAND OFF AUTO
Background color / foreground color	Aluminum / black
Dimensions	2" wide x 1 7/16" top to center line

Mounting/wiring:	
Mounting type	Rear
Mounting torque	177 lb in. (14.75 lb ft.)
Mounting diameter	30.5 mm
Wire connection type / torque	Screw-type terminals / 7 lb in. - 9 lb in.
Solid & stranded conductors	2 x (18 - 12 AWG) CU 60/75°C
Wires included	Yes
Certificates/approvals:	
	ISO 9001 certification
Additional information:	
	Instruction Sheet

