

Plug-in relay 1 change-over contact, hard gold-plated 24 V DC, for LZS sockets



Product brand name	SIRIUS
Product designation	Plug-in relay
Product type designation	LZX
<b>General technical data</b>	
Consumed active power	400 mW
Percental drop-out voltage related to the input voltage	10 %
Shock resistance	
• acc. to IEC 60068-2-27	5g / 11 ms
Vibration resistance	
• acc. to IEC 60068-2-6	30 ... 150 Hz: 5g
Switching behavior	monostable
Design of the switching function	changeover switch
Design of the switching function positively driven	No
Mechanical service life (switching cycles)	
• typical	30 000 000
Electrical endurance (switching cycles)	
• at AC-15 at 230 V typical	100 000
Thermal current	16 A

Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Reference code acc. to DIN EN 81346-2	K
Reference code acc. to DIN EN 61346-2	K

#### Control circuit/ Control

<b>Control supply voltage at DC</b>	
• rated value	24 V
<b>Operating range factor control supply voltage rated value at DC</b>	
• initial value	0.9
• Full-scale value	1.4
<b>Design of the relay operating mechanism</b>	poled
<b>Product component Plug-in socket</b>	No

#### Auxiliary circuit

<b>Type of switching contact</b>	Changeover contact
<b>Material of switching contacts</b>	AgNi 90/10-HTV
<b>Number of NC contacts for auxiliary contacts</b>	0
<b>Number of NO contacts for auxiliary contacts</b>	0
<b>Number of CO contacts</b>	
• for auxiliary contacts	1
<b>Operating current of auxiliary contacts at AC-15</b>	
• at 250 V	6 A

#### Main circuit

<b>Type of voltage</b>	DC
------------------------	----

#### Outputs

<b>Ampacity of the output relay at AC-15</b>	
• at 250 V at 50/60 Hz	6 A




#### Connections/ Terminals

<b>Product function</b>	
• removable terminal	No

#### Installation/ mounting/ dimensions

<b>Mounting position</b>	any
<b>Mounting type</b>	base mounting
<b>Height</b>	29 mm
<b>Width</b>	12.7 mm
<b>Depth</b>	19.5 mm

#### Certificates/ approvals

General Product Approval	Declaration of Conformity	other
 UR	  EG-Konf.	<a href="#">Miscellaneous</a> <a href="#">Confirmation</a>

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=LZX:RT315024>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=LZX:RT315024>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/LZX:RT315024>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=LZX:RT315024&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=LZX:RT315024&lang=en)

last modified:

11/20/2019