

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7064-4CH71-1KA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data | | Mechanical data | | | |
|---------------------------|-------------------------|-----------------------------|------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Rated speed (100 K) | 4500 rpm | Motor type | Permanent-magnet synchronous motor | | |
| Number of poles | 6 | Motor type | High Dynamic | | |
| Rated torque (100 K) | 5.0 Nm | Shaft height | 63 | | |
| Rated current | 7.0 A | Cooling | Natural cooling | | |
| Static torque (60 K) | 10.00 Nm | Radial runout tolerance | 0.040 mm | | |
| Static torque (100 K) | 12.0 Nm | Concentricity tolerance | 0.10 mm | | |
| Stall current (60 K) | 12.20 A | Axial runout tolerance | 0.10 mm | | |
| Stall current (100 K) | 15.00 A | Vibration severity grade | Grade A | | |
| Moment of inertia | 7.500 kgcm ² | Connector size | 1 | | |
| Efficiency | 93.0 % | Degree of protection | IP65 | | |
| Physical constants | | Design acc. to Code I | IM B5 (IM V1, IM V3) | | |
| | | Torque constant | 0.80 Nm/A | Temperature monitoring | Pt1000 temperature sensor |
| | | Voltage constant at 20° C | 50.5 V/1000*min ⁻¹ | Electrical connectors | Connectors for signals and power rotatable |
| | | Winding resistance at 20° C | 0.17 Ω | Color of the housing | Standard (Anthracite RAL 7016) |
| | | Rotating field inductance | 6.2 mH | Holding brake | without holding brake |
| | | Electrical time constant | 36.50 ms | Shaft extension | Feather key |
| | | Mechanical time constant | 0.60 ms | Encoder system | Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |
| | | Thermal time constant | 55 min | | |
| | | Shaft torsional stiffness | 29500 Nm/rad | | |
| | | Net weight of the motor | 15.4 kg | | |



Figure similar

MLFB-Ordering data

1FK7064-4CH71-1KA1

| Optimum operating point | | Recommended Motor Module | |
|-----------------------------------|----------|--------------------------|----------|
| Optimum speed | 3500 rpm | Rated inverter current | 18 A |
| Optimum power | 2.8 kW | Maximum inverter current | 54 A |
| Limiting data | | Maximum torque | 32.00 Nm |
| Max. permissible speed (mech.) | 7500 rpm | | |
| Max. permissible speed (inverter) | 7500 rpm | | |
| Maximum torque | 32.0 Nm | | |
| Maximum current | 46.0 A | | |