

T4, T5, T5HO

| Order code | Description | Watts (W) | Base | Color temp. (K) | Lumen output (lm) | Mean lumens (lm) | Rated life IS (3 hrs) | Rated life IS (12 hrs) | CRI | Nominal length in. (mm) | Efficacy (lm/W) | Case qty (master) |
|---------------------|------------------------------|--------------|------|--------------------|----------------------|---------------------|--------------------------|---------------------------|-----|----------------------------|--------------------|----------------------|
| T4 | | | | | | | | | | | | |
| Ø 15/32 in. (12 mm) | | | | | | | | | | | | |
| 10627 | F8T4/41K/330mm/G5/STD | 8 | G5 | 3 500 | 380 | 357 | 7 000 | 8 000 | 80 | 13 (330) | 48 | 200 |
| 10628 ¹ | F10T4/41K/309mm/G5/STD | 10 | G5 | 4 100 | 500 | 470 | 7 000 | 8 000 | 80 | 12 (305) | 50 | 48 |
| 10629 ¹ | F12T4/41K/430mm/G5/STD | 12 | G5 | 4 100 | 600 | 564 | 7 000 | 8 000 | 80 | 17 (430) | 50 | 48 |
| 10617 ¹ | F16T4/35K/475mm/G5/STD | 16 | G5 | 3 500 | 1 000 | 940 | 7 000 | 8 000 | 80 | 19 (475) | 63 | 200 |
| 10630 | F16T4/41K/475MM/G5 | 16 | G5 | 4 100 | 1 000 | 940 | 7 000 | 8 000 | 80 | 19 (475) | 63 | 48 |
| 10631 ¹ | F20T4/41K/520mm/G5/STD | 20 | G5 | 4 100 | 1 280 | 1 203 | 7 000 | 8 000 | 80 | 20 (520) | 64 | 48 |
| T5 | | | | | | | | | | | | |
| Ø 5/8 in. (16 mm) | | | | | | | | | | | | |
| 58977 | F4T5/CW/PH/G5/STD | 4 | G5 | 4 100 | 140 | 130 | 6 000 | 8 000 | 85 | 6 (152) | 35 | 100 |
| 58981 | F4T5/DL/PH/G5/STD | 4 | G5 | 6 500 | 120 | 115 | 6 000 | 8 000 | 82 | 6 (152) | 30 | 100 |
| 58978 | F6T5/CW/PH/G5/STD | 6 | G5 | 4 100 | 280 | 265 | 6 000 | 8 000 | 85 | 9 (229) | 47 | 100 |
| 58980 | F6T5/DL/PH/G5/STD | 6 | G5 | 6 500 | 240 | 230 | 6 000 | 8 000 | 82 | 9 (229) | 40 | 100 |
| 58976 | F8T5/WW/PH/G5/STD | 8 | G5 | 3 000 | 450 | 420 | 6 000 | 8 000 | 85 | 12 (305) | 56 | 100 |
| 58979 | F8T5/CW/PH/G5/STD | 8 | G5 | 4 100 | 420 | 400 | 6 000 | 8 000 | 85 | 12 (305) | 53 | 100 |
| 58974 | F8T5/DL/PH/G5/STD | 8 | G5 | 6 500 | 400 | 380 | 6 000 | 8 000 | 82 | 12 (305) | 50 | 100 |
| 10600 | F14T5/30K/8/PS/G5/STD | 14 | G5 | 3 000 | 1 350 | 1 280 | 24 000 | 30 000 | 85 | 22 (559) | 96 | 25 |
| 10601 | F14T5/35K/8/PS/G5/STD | 14 | G5 | 3 500 | 1 350 | 1 280 | 24 000 | 30 000 | 85 | 22 (559) | 96 | 25 |
| 10602 | F14T5/41K/8/PS/G5/STD | 14 | G5 | 4 100 | 1 350 | 1 280 | 24 000 | 30 000 | 85 | 22 (559) | 96 | 25 |
| 10603 | F21T5/30K/8/PS/G5/STD | 21 | G5 | 3 000 | 2 100 | 1 995 | 24 000 | 30 000 | 85 | 34 (864) | 100 | 25 |
| 10604 | F21T5/35K/8/PS/G5/STD | 21 | G5 | 3 500 | 2 100 | 1 995 | 24 000 | 30 000 | 85 | 34 (864) | 100 | 25 |
| 10605 | F21T5/41K/8/PS/G5/STD | 21 | G5 | 4 100 | 2 100 | 1 995 | 24 000 | 30 000 | 85 | 34 (864) | 100 | 25 |
| 10606 | F28T5/30K/8/PS/G5/STD | 28 | G5 | 3 000 | 2 900 | 2 755 | 24 000 | 30 000 | 85 | 46 (1 168) | 104 | 25 |
| 10607 | F28T5/35K/8/PS/G5/STD | 28 | G5 | 3 500 | 2 900 | 2 755 | 24 000 | 30 000 | 85 | 46 (1 168) | 104 | 25 |
| 10608 | F28T5/41K/8/PS/G5/STD | 28 | G5 | 4 100 | 2 900 | 2 755 | 24 000 | 30 000 | 85 | 46 (1 168) | 104 | 25 |
| 58121 | F28T5/50K/8/PS/G5/STD | 28 | G5 | 5 000 | 2 750 | 2 610 | 24 000 | 30 000 | 85 | 46 (1 168) | 98 | 25 |
| 10609 | F35T5/30K/8/PS/G5/STD | 35 | G5 | 3 000 | 3 650 | 3 450 | 24 000 | 30 000 | 85 | 58 (1 473) | 104 | 25 |
| 10610 | F35T5/35K/8/PS/G5/STD | 35 | G5 | 3 500 | 3 650 | 3 450 | 24 000 | 30 000 | 85 | 58 (1 473) | 104 | 25 |
| 10611 | F35T5/41K/8/PS/G5/STD | 35 | G5 | 4 100 | 3 650 | 3 450 | 24 000 | 30 000 | 85 | 58 (1 473) | 104 | 25 |
| T5HO | | | | | | | | | | | | |
| Ø 5/8 in. (16 mm) | | | | | | | | | | | | |
| 10238 | F24T5/30K/8/HO/PS/G5/STD | 24 | G5 | 3 000 | 2 000 | 1 900 | 24 000 | 30 000 | 85 | 22 (559) | 83 | 25 |
| 10239 | F24T5/35K/8/HO/PS/G5/STD | 24 | G5 | 3 500 | 2 000 | 1 900 | 24 000 | 30 000 | 85 | 22 (559) | 83 | 25 |
| 10237 | F24T5/41K/8/HO/PS/G5/STD | 24 | G5 | 4 100 | 2 000 | 1 900 | 24 000 | 30 000 | 85 | 22 (559) | 83 | 25 |
| 10240 | F39T5/30K/8/HO/PS/G5/STD | 39 | G5 | 3 000 | 3 500 | 3 325 | 24 000 | 30 000 | 85 | 34 (864) | 90 | 25 |
| 10241 | F39T5/35K/8/HO/PS/G5/STD | 39 | G5 | 3 500 | 3 500 | 3 325 | 24 000 | 30 000 | 85 | 34 (864) | 90 | 25 |
| 10242 | F39T5/41K/8/HO/PS/G5/STD | 39 | G5 | 4 100 | 3 500 | 3 325 | 24 000 | 30 000 | 85 | 34 (864) | 90 | 25 |
| 60016 | F49T5/30K/8/HO/PS/G5/STD ESV | 49 | G5 | 3 000 | 4 900 | 4 650 | 24 000 | 30 000 | 85 | 46 (1 168) | 100 | 25 |
| 60017 | F49T5/35K/8/HO/PS/G5/STD ESV | 49 | G5 | 3 500 | 4 900 | 4 650 | 24 000 | 30 000 | 85 | 46 (1 168) | 100 | 25 |
| 60018 | F49T5/41K/8/HO/PS/G5/STD ESV | 49 | G5 | 4 100 | 4 900 | 4 650 | 24 000 | 30 000 | 85 | 46 (1 168) | 100 | 25 |
| 65493 | F54T5/30K/8/HO/PS/G5/STD | 54 | G5 | 3 000 | 5 000 | 4 656 | 35 000 | 40 000 | 85 | 46 (1 168) | 86 | 25 |
| 65496 | F54T5/41K/8/HO/PS/G5/STD | 54 | G5 | 4 100 | 5 000 | 4 638 | 35 000 | 40 000 | 85 | 46 (1 168) | 96 | 25 |
| 65498 | F54T5/50K/8/HO/PS/G5/STD | 54 | G5 | 5 000 | 4 900 | 4 465 | 35 000 | 40 000 | 85 | 46 (1 168) | 83 | 25 |
| 65499 | F54T5/65K/8/HO/PS/G5/STD | 54 | G5 | 6 500 | 4 750 | 4 434 | 35 000 | 40 000 | 85 | 46 (1 168) | 82 | 25 |
| 10613 ² | F54T5/FS/HO/PS/G5/STD | 54 | G5 | 5 700 | 5 000 | 4 750 | 24 000 | 30 000 | 92 | 46 (1 168) | 93 | 25 |
| 10248 | F80T5/41K/8/HO/PS/G5/STD | 80 | G5 | 4 100 | 7 000 | 6 650 | 24 000 | 30 000 | 85 | 58 (1 473) | 88 | 25 |

IS=Instant Start ballast PS=Program Start ballast PRS=Program Rapid Start ballast

¹ Not TCLP Compliant
² This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.
³ One year warranty on lamps with less than 18 000 hours average life
⁴ Two year warranty on lamps with more than 18 000 hours average life



T8

| Order code | Description | Watts (W) | Base | Color temp. (K) | Rated life IS (3 hrs) | Rated life IS (12 hrs) | Rated life PS/PRS (3 hrs) | Rated life PS/PRS (12 hrs) | Lumen output (lm) | Mean lumens (lm) | CRI | Nominal length in. (mm) | Efficacy (lm/W) | Case qty (master) |
|----------------------------------------|---------------------------------|-----------|------|-----------------|-----------------------|------------------------|---------------------------|----------------------------|-------------------|------------------|-----|-------------------------|-----------------|-------------------|
| T8 Ø 1 in. (26 mm) | | | | | | | | | | | | | | |
| 10426 | F13T8/CW/PH/G13/STD | 13 | G13 | 4 100 | 6 000 | 7 500 | N/A | N/A | 530 | 498 | 62 | 12 (305) | 41 | 48 |
| 67802 | F14T8/CW/PH/G13/STD | 14 | G13 | 4 000 | N/A | N/A | N/A | N/A | 710 | 710 | 60 | 15 (381) | 51 | 200 |
| 10634 | F14T8/DL/PH/G13/STD | 14 | G13 | 6 500 | 6 000 | 7 500 | N/A | N/A | 575 | 541 | 62 | 15 (381) | 41 | 48 |
| 62021 | F15T8/WW/PH/G13/STD | 15 | G13 | 3 000 | N/A | N/A | 24 000 | 30 000 | 900 | 800 | 50 | 18 (457) | 60 | 25 |
| 62022 | F15T8/CW/PH/G13/STD | 15 | G13 | 4 100 | N/A | N/A | 24 000 | 30 000 | 850 | 750 | 60 | 18 (457) | 57 | 25 |
| 62023 | F15T8/DL/PH/G13/STD | 15 | G13 | 6 500 | N/A | N/A | 24 000 | 30 000 | 800 | 700 | 75 | 18 (457) | 53 | 25 |
| 700 series Ø 1 in. (26 mm) | | | | | | | | | | | | | | |
| 10010 | F17T8/35K/7/RS/G13/STD ESV | 17 | G13 | 3 500 | N/A | N/A | 24 000 | 30 000 | 1 300 | 1 235 | 75 | 24 (610) | 76 | 25 |
| 10011 | F17T8/41K/7/RS/G13/STD ESV | 17 | G13 | 4 100 | N/A | N/A | 24 000 | 30 000 | 1 300 | 1 235 | 75 | 24 (610) | 76 | 25 |
| 10794 | F25T8/35K/7/RS/G13/STD ESV | 25 | G13 | 3 500 | 24 000 | 30 000 | 30 000 | 36 000 | 2 000 | 1 800 | 75 | 36 (915) | 80 | 25 |
| 65485 | F25T8/41K/7/RS/G13/STD ESV | 25 | G13 | 4 100 | 24 000 | 30 000 | 30 000 | 36 000 | 2 000 | 1 800 | 75 | 36 (915) | 80 | 25 |
| 51165 | F32T8/50K/7/RS/G13/STD ESV | 32 | G13 | 5 000 | 20 000 | 24 000 | 24 000 | 30 000 | 2 800 | 2 650 | 75 | 48 (1 220) | 88 | 25 |
| 800 series Ø 1 in. (26 mm) | | | | | | | | | | | | | | |
| 10014 | F17T8/30K/8/RS/G13/STD ESV | 17 | G13 | 3 000 | N/A | N/A | 24 000 | 30 000 | 1 400 | 1 330 | 85 | 24 (610) | 82 | 25 |
| 10015 | F17T8/35K/8/RS/G13/STD ESV | 17 | G13 | 3 500 | N/A | N/A | 24 000 | 30 000 | 1 400 | 1 330 | 85 | 24 (610) | 82 | 25 |
| 10002 | F17T8/41K/8/RS/G13/STD ESV | 17 | G13 | 4 100 | N/A | N/A | 24 000 | 30 000 | 1 400 | 1 330 | 85 | 24 (610) | 82 | 25 |
| 65483 | F25T8/30K/8/RS/G13/STD ESV | 25 | G13 | 3 000 | 24 000 | 30 000 | 30 000 | 36 000 | 2 150 | 2 040 | 85 | 36 (915) | 86 | 25 |
| 65484 | F25T8/35K/8/RS/G13/STD ESV | 25 | G13 | 3 500 | 24 000 | 30 000 | 30 000 | 36 000 | 2 575 | 2 450 | 85 | 36 (915) | 85 | 25 |
| 58635 | F25T8/830HL/ES/STD | 25 | G13 | 3 000 | 24 000 | 30 000 | 40 000 | 42 000 | 2 400 | 2 300 | 85 | 48 (1 220) | 96 | 25 |
| 65486 | F25T8/41K/8/RS/G13/STD ESV | 25 | G13 | 4 100 | 24 000 | 30 000 | 30 000 | 36 000 | 2 150 | 2 040 | 85 | 36 (915) | 86 | 25 |
| 58635 | F25T8/830HL/ES/STD | 25 | G13 | 3 000 | 24 000 | 30 000 | 40 000 | 42 000 | 2 400 | 2 300 | 85 | 48 (1 220) | 96 | 25 |
| 57124 | F25T8/835HL/ES/STD | 25 | G13 | 3 500 | 24 000 | 30 000 | 40 000 | 42 000 | 2 400 | 2 300 | 85 | 48 (1 220) | 96 | 25 |
| 57122 | F25T8/841HL/ES/STD | 25 | G13 | 4 100 | 24 000 | 30 000 | 40 000 | 42 000 | 2 400 | 2 300 | 85 | 48 (1 220) | 96 | 25 |
| 56505 | F28T8/830HL/ES/STD | 28 | G13 | 3 000 | 24 000 | 30 000 | 40 000 | 42 000 | 2 725 | 2 560 | 85 | 48 (1 220) | 97 | 25 |
| 56506 | F28T8/835HL/ES/STD | 28 | G13 | 3 500 | 24 000 | 30 000 | 40 000 | 42 000 | 2 725 | 2 560 | 85 | 48 (1 220) | 97 | 25 |
| 65490 | F28T8/841HL/ES/STD | 28 | G13 | 4 100 | 24 000 | 30 000 | 40 000 | 42 000 | 2 725 | 2 560 | 85 | 48 (1 220) | 97 | 25 |
| 56501 | F30T8/830HL/ES/STD | 30 | G13 | 3 000 | 24 000 | 30 000 | 40 000 | 42 000 | 2 850 | 2 700 | 86 | 48 (1 220) | 95 | 25 |
| 56502 | F30T8/835HL/ES/STD | 30 | G13 | 3 500 | 24 000 | 30 000 | 40 000 | 42 000 | 2 850 | 2 700 | 86 | 48 (1 220) | 95 | 25 |
| 56503 | F30T8/841HL/ES/STD | 30 | G13 | 4 100 | 24 000 | 30 000 | 40 000 | 42 000 | 2 850 | 2 700 | 86 | 48 (1 220) | 95 | 25 |
| 56504 | F30T8/850HL/ES/STD | 30 | G13 | 5 000 | 24 000 | 30 000 | 40 000 | 42 000 | 2 750 | 2 600 | 86 | 48 (1 220) | 92 | 25 |
| 62981 | F32T8/30K/8/RS/G13/STD ESV BULK | 32 | G13 | 3 000 | 24 000 | 30 000 | 40 000 | 42 000 | 3 050 | 2 900 | 85 | 48 (1 220) | 95 | 25 |
| 62982 | F32T8/35K/8/RS/G13/STD ESV BULK | 32 | G13 | 3 500 | 24 000 | 30 000 | 40 000 | 42 000 | 3 050 | 2 900 | 85 | 48 (1 220) | 95 | 25 |
| 59898 | F32T8/41K/8/RS/G13/STD ESV BULK | 32 | G13 | 4 100 | 24 000 | 30 000 | 40 000 | 42 000 | 3 050 | 2 900 | 85 | 48 (1 220) | 94 | 25 |
| 62984 | F32T8/65K/8/RS/G13/STD ESV BULK | 32 | G13 | 6 500 | 24 000 | 30 000 | 40 000 | 42 000 | 2 900 | 2 750 | 85 | 48 (1 220) | 91 | 25 |
| 900 series Ø 1 in. (26 mm) | | | | | | | | | | | | | | |
| 65492 ² | F32T8/50K/9/RS/G13/STD ESV | 32 | G13 | 5 000 | 15 000 | 24 000 | 20 000 | 28 000 | 2 100 | 2 000 | 95 | 48 (1 220) | 66 | 25 |
| 51174 ⁴ | F32T8/FS/RS/G13/STD | 32 | G13 | 5 700 | 20 000 | 24 000 | 24 000 | 30 000 | 2 300 | 2 185 | 92 | 48 (1 220) | 72 | 25 |
| T8 XL31 Ø 1 in. (26 mm) | | | | | | | | | | | | | | |
| 10914 | F32T8/830K/XL31/STD | 32 | G13 | 3 000 | 20 000 | 24 000 | 24 000 | 30 000 | 3 100 | 2 950 | 89 | 48 (1 220) | 97 | 25 |
| 10915 | F32T8/835K/XL31/STD | 32 | G13 | 3 500 | 20 000 | 24 000 | 24 000 | 30 000 | 3 100 | 2 950 | 89 | 48 (1 220) | 97 | 25 |
| 10916 | F32T8/841K/XL31/STD | 32 | G13 | 4 100 | 20 000 | 24 000 | 24 000 | 30 000 | 3 100 | 2 950 | 89 | 48 (1 220) | 97 | 25 |
| 10917 | F32T8/850K/XL31/STD | 32 | G13 | 5 000 | 20 000 | 24 000 | 24 000 | 30 000 | 3 000 | 2 850 | 89 | 48 (1 220) | 94 | 25 |
| T8 Long Life Ø 1 in. (26 mm) | | | | | | | | | | | | | | |
| 60855 ⁵ | F28T8/35K/8/RS/G13/STD ESV LL | 28 | G13 | 3 500 | 36 000 | 40 000 | 55 000 | 60 000 | 2 675 | 2 540 | 85 | 48 (1 220) | 96 | 25 |
| 60856 ^{1,5} | F32T8/50K/8/RS/G13/STD ESV LL | 32 | G13 | 5 000 | 36 000 | 40 000 | 55 000 | 60 000 | 2 850 | 2 700 | 85 | 48 (1 220) | 89 | 25 |

IS=Instant Start ballast PS=Program Start ballast PRS=Program Rapid Start ballast
¹This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.
²One year warranty on lamps with less than 18 000 hours average life
³Two year warranty on lamps with more than 18 000 hours average life



T12

| Order code | Description | Watts (W) | Base | Color temp. (K) | Rated life PS/PRS (3 hrs) | Lumen output (lm) | Mean lumens (lm) | CRI | Nominal length in. (mm) | Efficacy (lm/W) | Case qty (inner/master) |
|------------------------------------------|-------------------------|-----------|------|-----------------|---------------------------|-------------------|------------------|-----|-------------------------|-----------------|-------------------------|
| 900 series Ø 1 1/2 in. (38 mm) | | | | | | | | | | | |
| 64251 | F40T12/41K/9/RS/G13/STD | 40 | G13 | 4 100 | 24 000 | 2 500 | 2 500 | 90 | 48 (1 220) | 63 | 30 |
| 64252 | F40T12/50K/9/RS/G13/STD | 40 | G13 | 5 000 | 24 000 | 2 250 | 2 250 | 90 | 48 (1 220) | 56 | 30 |
| 64253 | F40T12/65K/9/RS/G13/STD | 40 | G13 | 6 500 | 24 000 | 2 250 | 2 250 | 90 | 48 (1 220) | 56 | 30 |

Circline & U-Bent

| Order code | Description | Watts (W) | Base | Color temp. (K) | Lumen output (lm) | Mean lumens (lm) | Rated life IS (3 hrs) | CRI | Nominal length in. (mm) | Efficacy (lm/W) | Case qty (master) |
|-----------------------------------------|---------------------|-----------|--------|-----------------|-------------------|------------------|-----------------------|-----|-------------------------|-----------------|-------------------|
| Circline Ø 1 3/16 in. (30 mm) | | | | | | | | | | | |
| 58984 | FC6T9/CW/RS/4P/STD | 20 | G10q-4 | 4 100 | 890 | 850 | 10 000 | 82 | 7 (165) | 45 | 12 |
| 58985 | FC8T9/WW/RS/4P/STD | 22 | G10q-4 | 3 000 | 1 450 | 1 380 | 10 000 | 82 | 8 (210) | 66 | 12 |
| 58983 | FC8T9/CW/RS/4P/STD | 22 | G10q-4 | 4 100 | 1 350 | 1 280 | 10 000 | 82 | 8 (210) | 61 | 24 |
| 58982 | FC8T9/DL/RS/4P/STD | 22 | G10q-4 | 6 500 | 1 210 | 1 150 | 10 000 | 82 | 8 (210) | 55 | 24 |
| 58986 | FC12T9/CW/RS/4P/STD | 32 | G10q-4 | 4 100 | 2 300 | 2 185 | 10 000 | 82 | 12 (305) | 72 | 24 |
| 58987 | FC12T9/DL/RS/4P/STD | 32 | G10q-4 | 6 500 | 2 000 | 1 900 | 10 000 | 82 | 12 (305) | 63 | 12 |
| 58988 | FC16T9/CW/RS/4P/STD | 40 | G10q-4 | 4 100 | 3 150 | 3 000 | 10 000 | 82 | 16 (406) | 79 | 12 |

U-bent Lamp

Ø 1 in. (26 mm)

T8 800 series

| | | | | | | | | | | | |
|-------|--------------------------------|----|-----|-------|-------|-------|--------|----|------------|----|----|
| 58698 | FB31T8/35K/8/U1/RS/G13/STD | 31 | G13 | 3 500 | 2 750 | 2 610 | 24 000 | 82 | 22.5 (572) | 89 | 20 |
| 65500 | FB32T8/30K/8/U6/RS/G13/STD ESV | 28 | G13 | 3 000 | 2 800 | 2 772 | 20 000 | 85 | 22.5 (572) | 85 | 20 |
| 65501 | FB32T8/35K/8/U6/RS/G13/STD ESV | 31 | G13 | 3 000 | 2 800 | 2 825 | 20 000 | 85 | 22.5 (572) | 85 | 20 |
| 65502 | FB32T8/41K/8/U6/RS/G13/STD ESV | 32 | G13 | 4 100 | 2 800 | 2 550 | 20 000 | 85 | 22.5 (572) | 88 | 20 |
| 65503 | FB32T8/50K/8/U6/RS/G13/STD ESV | 32 | G13 | 5 000 | 2 750 | 2 500 | 20 000 | 86 | 22.5 (572) | 86 | 20 |

T8 900 series

Ø 1 1/2 in. (38 mm)

| | | | | | | | | | | | |
|-------|-----------------------------|----|-----|-------|-------|-------|--------|----|------------|----|----|
| 64255 | FB40T12/41K/9/U6/RS/G13/STD | 40 | G13 | 4 100 | 2 250 | 2 500 | 24 000 | 90 | 22.6 (574) | 63 | 12 |
| 64256 | FB40T12/65K/9/U6/RS/G13/STD | 40 | G13 | 6 500 | 2 250 | 2 250 | 24 000 | 90 | 22.6 (574) | 56 | 12 |

IS=Instant Start ballast PS=Program Start ballast PRS=Program Rapid Start ballast

¹ This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.
² One year warranty on lamps with less than 18 000 hours average life
³ Two year warranty on lamps with more than 18 000 hours average life

