

SITOR fuse-disconnector 22x 58, Up to 100 A, 690 V AC



Model	
Product designation	SITOR fuse switch disconnecter
Design of the operating mechanism	others
General technical data	
Number of poles	3
Size of fuse link	Other
Usage category	AC20B/690 V
Size of the fuse link	22 x 58 mm
Operating voltage	
<ul style="list-style-type: none"> • at AC / rated value / maximum • at DC / rated value / maximum 	<p>690 V</p> <p>800 V</p>
Protection class	
Protection class IP / on the front	Other
Current	
Continuous current / rated value	100 A
Suitability	
Suitability for use	

• Main switch	No
• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes

Product function

Product function / fuse monitoring	No
------------------------------------	----

Short circuit

Conditional short-circuit current (I _q) / rated value	100 kA
---	--------

Connections

Connectable conductor cross-section	
• solid	4 ... 50 mm ²
• stranded	4 ... 50 mm ²
Type of electrical connection / for main current circuit	screw-type terminals

Mechanical Design

Height	70 mm
Depth	118 mm
Mounting type	
• floor mounting	No
• front mounting	Yes
• rail mounting	No
Net weight	471 g

Certificates

Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval

Declaration of Conformity



[Miscellaneous](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3NC2293>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC2293>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3NC2293

CAX-Online-Generator

<http://www.siemens.com/cax>



