

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7044-7AH71-1KA2

No image available for this configuration.

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data	
Rated speed (100 K)	4500 rpm
Number of poles	6
Rated torque (100 K)	3.0 Nm
Rated current	4.9 A
Static torque (60 K)	3.00 Nm
Static torque (100 K)	4.0 Nm
Stall current (60 K)	4.60 A
Stall current (100 K)	6.30 A
Moment of inertia	1.280 kgcm ²
Efficiency	91.0 %

Physical constants	
Torque constant	0.63 Nm/A
Voltage constant at 20° C	42.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.81 Ω
Rotating field inductance	11.0 mH
Electrical time constant	13.50 ms
Mechanical time constant	0.78 ms
Thermal time constant	45 min
Shaft torsional stiffness	9500 Nm/rad
Net weight of the motor	7.7 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	without holding brake
Shaft extension	Feather key
Encoder system	Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

MLFB-Ordering data

1FK7044-7AH71-1KA2

Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	4500 rpm	Rated inverter current	9 A
Optimum power	1.4 kW	Maximum inverter current	18 A
Limiting data		Maximum torque	11.00 Nm
Max. permissible speed (mech.)	8000 rpm		
Max. permissible speed (inverter)	13300 rpm		
Maximum torque	12.0 Nm		
Maximum current	20.0 A		