

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7103-2AF71-1BA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data | | Mechanical data | | | |
|--|---------------------------|-----------------------------|------------------------------------|------------------------|---|
| Rated speed (100 K) | 3000 rpm | Motor type | Permanent-magnet synchronous motor | | |
| Number of poles | 8 | Motor type | Compact | | |
| Rated torque (100 K) | 14.0 Nm | Shaft height | 100 | | |
| Rated current | 11.5 A | Cooling | Natural cooling | | |
| Static torque (60 K) | 30.00 Nm | Radial runout tolerance | 0.050 mm | | |
| Static torque (100 K) | 36.0 Nm | Concentricity tolerance | 0.10 mm | | |
| Stall current (60 K) | 21.00 A | Axial runout tolerance | 0.10 mm | | |
| Stall current (100 K) | 26.00 A | Vibration severity grade | Grade A | | |
| Moment of inertia | 104.000 kgcm ² | Connector size | 1.5 | | |
| Efficiency | 93.0 % | Degree of protection | IP64 | | |
| <th colspan="2">Physical constants</th> <td>Design acc. to Code I</td> <td>IM B5 (IM V1, IM V3)</td> | | Physical constants | | Design acc. to Code I | IM B5 (IM V1, IM V3) |
| | | Torque constant | 1.35 Nm/A | Temperature monitoring | Pt1000 temperature sensor |
| | | Voltage constant at 20° C | 89.5 V/1000*min ⁻¹ | Electrical connectors | Connectors for signals and power rotatable |
| | | Winding resistance at 20° C | 0.09 Ω | Color of the housing | Standard (Anthracite RAL 7016) |
| | | Rotating field inductance | 2.4 mH | Holding brake | without holding brake |
| | | Electrical time constant | 27.00 ms | Shaft extension | Feather key |
| | | Mechanical time constant | 1.46 ms | Encoder system | Encoder AS24DQI: absolute encoder single-turn 24 bits |
| | | Thermal time constant | 65 min | | |
| | | Shaft torsional stiffness | 148000 Nm/rad | | |
| | | Net weight of the motor | 28.5 kg | | |



Figure similar

MLFB-Ordering data

1FK7103-2AF71-1BA0

| Optimum operating point | | Recommended Motor Module | |
|-----------------------------------|----------|--------------------------|-----------|
| Optimum speed | 2500 rpm | Rated inverter current | 30 A |
| Optimum power | 5.4 kW | Maximum inverter current | 90 A |
| Limiting data | | Maximum torque | 108.00 Nm |
| Max. permissible speed (mech.) | 5000 rpm | | |
| Max. permissible speed (inverter) | 5000 rpm | | |
| Maximum torque | 108.0 Nm | | |
| Maximum current | 84.0 A | | |