

SIMATIC PCS 7 Industrial Workstation IPC647D; (Rack PC, 19", 2HE), Interfaces: 2x Gbit LAN (RJ45), 1x DVI-I, 2x Display Port; 1x COM, 2x PS/2, Audio; 2x USB 3.0; 2x USB 2.0 on rear, 1x USB 3.0; 1x USB 2.0, on front; 1x USB 3.0 internal; Temperature and fan monitoring Watchdog; card retainer; Xeon E3-1268LV3 (4C/8T, 2.3 GHz, 8 MB cache, TB, VT-D, AMT); ES/OS Single Station; RAID1, 240 GB (2 x 240 GB SSD, (EMLC) SATA, data mirroring); in removable frame; hot swap; front-side 16 GB DDR3 SDRAM (2x 8 GB), ECC, dual channel; BCE; PCS 7 V9.0 SP2 pre-installed Windows 10 IoT Enterprise 2015 LTSP, 64 bit, MUI (en, de, fr, it, es, cn) bus module 4 slots: 1x PCIE X16 (8 lane), 3x PCIE X16 (4 lane); DVD +/-RW (slim); + multi monitor 2 screens VIA Onboard interfaces + 1x adapter cable (Display Port according to DVI-D); 2 x 100/240V redund. power supply unit; without power supply cable

last modified:

1/31/2021 