

Kellems Wire Management, Cord Connectors, European Style .25-.48", 3/4", Gray

By Hubbell Wiring Device-Kellems
Catalog # [SEC75RGA](#)



Kellems Wire Management, Cord Connectors, European Style
.25-.48", 3/4", Gray

Features

- European Style .25-.48"
- 3/4"
- Gray

Application

Straight Male

Performance

Flammability - UL 94X-2

General

Catalog Number	SEC75RGA
Color	Gray
EU RoHS Indicator	No
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
Item Type	Low Profile NPT Cord Connectors
Material	Nylon
Material - Mounting Hardware	Locknut or Tapped Opening
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	-22 Deg F to 225 Deg F (-30 Deg C to 107 Deg C)
Temperature Rating	Minimum -22°F to 225°F (-30°C to 107°C).
Type	Low Profile NPT Cord Connectors
UPC	783585346915

Dimensions

Display Size 3/4" NPT

Conductor Related

Conductor Range 0.25-0.48 in (6.35-12.19 mm)
Number of Conductors Single

Certifications And Compliance

Industry Standard(s) UL Listing File E-41567, UL Recognition File E-41567;CSA File LR27378C, VDE Marks Licence #136681
Nema Rating IP66

Logistics

Carton Quantity 50

Product Assets

[Catalog Page - WDK W-74](#) [Catalog Page - WDK W-73](#) [Catalog Page - WDK W-73](#) [Catalog Page - WDK W-73](#) [Catalog Page - WDK W-73](#) [Catalog Page - WDK W-73](#) [Catalogs - WDK Catalog Full 2024](#) [Literature - Wire Management Solutions Brochure](#) [Literature - FOOD & BEVERAGE SOLUTIONS](#) [Literature - PULP & PAPER SOLUTIONS](#) [Literature - Pulp & Paper Solutions](#) [Literature - FOOD & BEVERAGE SOLUTIONS](#) [Specifications - SEC75RGA](#) [Warranty - Industrial & Commercial Products](#) [Video - Kellems Wire Management Solutions](#)