

## Data sheet for SIMOTICS S-1FK7

No image available for this configuration.

MLFB-Ordering data

1FK7060-5AH71-1GG0

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data	
Rated speed (100 K)	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	8	Motor type	Compact
Rated torque (100 K)	3.7 Nm	Shaft height	63
Rated current	4.1 A	Cooling	Natural cooling
Static torque (60 K)	5.00 Nm	Radial runout tolerance	0.040 mm
Static torque (100 K)	6.0 Nm	Concentricity tolerance	0.10 mm
Stall current (60 K)	5.1 A	Axial runout tolerance	0.10 mm
Stall current (100 K)	6.2 A	Vibration severity grade	Grade A
Moment of inertia	7.950 kgcm <sup>2</sup>	Connector size	1
Efficiency	90.0 %	Degree of protection	IP64
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
Torque constant	0.95 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
Voltage constant at 20° C	60.5 V/1000*min <sup>-1</sup>	Electrical connectors	Connectors for signals and power rotatable
Winding resistance at 20° C	0.73 Ω	Color of the housing	without
Rotating field inductance	7.0 mH	Holding brake	without holding brake
Electrical time constant	9.60 ms	Shaft extension	Plain shaft
Mechanical time constant	1.93 ms	Encoder system	Encoder AM32S/R: absolute encoder 32 S/R, 4096 revolutions multi-turn, with EnDat interface
Thermal time constant	30 min		
Shaft torsional stiffness	42000 Nm/rad		
Net weight of the motor	7.0 kg		

MLFB-Ordering data

1FK7060-5AH71-1GG0

Figure similar

## Optimum operating point

Optimum speed 4500 rpm

Optimum power 1.7 kW

## Limiting data

Max. permissible speed (mech.) 7200 rpm

Max. permissible speed (inverter) 9500 rpm

Maximum torque 18.0 Nm

Maximum current 19.5 A

## Recommended Motor Module

Rated inverter current 9 A

Maximum inverter current 18 A

Maximum torque 16.80 Nm