

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7082-5AC71-1FA1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	2000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact
Rated torque (100 K)	11.4 Nm	Shaft height	80 mm
Rated current	4.9 A	Cooling	Natural cooling
Static torque (60 K)	10.60 Nm	Radial runout tolerance	N
Static torque (100 K)	13.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	4.2 A	Degree of protection	IP65
Stall current (100 K)	5.0 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0026500 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	93.0 %	Color of the housing	Pearl dark grey RAL 9023
Physical constants		Holding brake version	no value
		Shaft end type	Fitted key and keyway
Torque constant	2.50 Nm/A	Sensor design	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Voltage constant at 20° C	159.5 V/1000*min ⁻¹	Electrical connectors	Connector turnable
Winding resistance at 20° C	1.38 Ω	Connector size	1
Rotating field inductance	21.0 mH		
Electrical time constant	15.00 ms		
Mechanical time constant	1.80 ms		
Thermal time constant	40 min		
Shaft torsional stiffness	76000 Nm/rad		
Net weight of the motor	14.0 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7082-5AC71-1FA1



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	5 A
Optimum power	2.4 kW	Maximum inverter current	15 A
Limiting data		Maximum torque	35.00 Nm
Max. permissible speed (mech.)	8000 rpm		
Max. permissible speed (inverter)	3500 rpm		
Maximum torque	52.0 Nm		
Maximum current	26.0 A		